



Main

Range of Product	PowerLogic T300
Product or Component Type	Voltage adaptor

Complementary

Rated voltage	11...36 kV
Input voltage limits	< 30 V
Network Frequency	50/60 Hz
Electrical connection	Output: connector RJ45 Input: wires

Environment

Product Certifications	CE
IP degree of protection	IP30 conforming to IEC 60529
IK degree of protection	IK07 IEC 62262
Ambient Air Temperature for Operation	-40...185 °F (-40...85 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Fire resistance	1562 °F (850 °C) IEC 60695-2-11
Environmental characteristic	Salt mist 200 h IEC 60068-2-11
Relative humidity	95 % IEC 60068-2-30
Operating altitude	<= 9842.52 ft (3000 m)
Height	0.39 in (10 mm)
Width	6.69 in (170 mm)
Length	9.45 in (240 mm)
Net Weight	0.55 lb(US) (0.25 kg)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.000 cm)
Package 1 Width	5.51 in (14.000 cm)
Package 1 Length	7.09 in (18.000 cm)
Package 1 Weight	1.69 oz (48 g)
Unit Type of Package 2	S02
Number of Units in Package 2	50
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	5.95 lb(US) (2.700 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.