



GREENLEE.
A Textron Company

MADE FOR THE TRADE!™

DMM, 1000V AC/DC (DM-200A)

Digital Multimeter



Image
Unavailable

Cat No: 52047801

UPC No: 783310087403

Description

- Measures voltage, current, resistance and frequency
- Tests continuity and diodes
- Backlit LCD with 6,000 count display
- Two voltage detection modes - non-contact or using a single test lead
- BeepJack warns when test leads are incorrectly inserted in current measurement terminals
- Automatic and manual range selection
- Relative offset mode to see changes in measurements
- Data hold
- Use optional USB / RS-232 interface DMSC-2U for direct-to-PC logging
- Lifetime Limited Warranty
- Accessories included: (2)1.5V AAA batteries, bead temperature probe (DM-210A, DM-510A only, 400°F/204°C max), test leads, protective boot

Specifications

- Amperage Measurement : 600, 6000 μ A; 60, 600mA; 6, 8A
- Battery : (2) 1.5 V AAA
- Capacitance : 60, 600 nF; 6, 60, 600, 3000 μ F
- Display : Backlit LCD With 6,000 Count
- Frequency Measurement : 10Hz - 50kHz Sine Wave, 5Hz - 999.9kHz Logic Level Square Wave
- Includes : (2) 1.5V AAA Batteries, Bead Temperature Probe (DM-210A, DM-510A Only, 400 DEG F/204 DEG C max), Test leads, ProtectiveBoot
- Measurement Category : CAT IV 300 V, CAT III 600 V, CAT II 1000 V
- Replacement Part : TSG-3 Sure-Grip Test Leads
- Resistance Measurement : 600 Ω ; 6, 60, 600 k Ω ; 6, 60 M Ω ;
- Standard : CAT IV, CAT II, C/UL US Listed, CAT III, CE Listed
- Sub Brand : ESM
- Temperature Rating : K Type, -58 To 1832°F (-50 To 1000°C)
- Type : Digital
- Voltage Measurement : 60, 600 mV; 6, 60, 600, 1000V