


TYPE ILSCONS

Features

- Color coded
- Funnel Entry
- Manufactured from high strength copper alloy
- Electro-tin plated
- Silver solder brazed seam
- Vinyl insulation
- Packaged in convenient small quantities
- UL Listed and CSA Certified for 600 volts, 90°C

Benefits

- Provides easy wire range identification
- #22-16 AWG Red
- #16-14 AWG Blue
- #12-10 AWG Yellow
- Provides maximum conductivity
- Provides low contact resistance
- May be crimped anywhere and will not split open, even under extreme operating stresses
- Provides tough pliable insulative qualities to protect connectors and wire from corrosion as well as providing some strain relief
- Attractive resealable packaging designed for merchandise racks
- Ensures reliability for copper conductor



Catalog Number	Wire Range	Length	Maximum Wire Insulated Diameter	Connector Type
44900-B100	16-22	.953	.145	Expanded Vinyl Insulated Butt Splices
44900-B1000	16-22	.953	.145	Expanded Vinyl Insulated Butt Splices
44910-B100	14-16	.953	.175	Expanded Vinyl Insulated Butt Splices
44910-B1000	14-16	.953	.175	Expanded Vinyl Insulated Butt Splices
44920-B50	10-12	1.024	.255	Expanded Vinyl Insulated Butt Splices
44920-B500	10-12	1.024	.255	Expanded Vinyl Insulated Butt Splices

Can be supplied in bulk. Consult factory for part number.

Other sizes available on request. Contact factory for pricing.