



Main

Range of Product	Altivar
Range Compatibility	Altivar 312 Altivar 61 Altivar Lift Altivar 32 Altivar Machine ATV320 Altivar 312 Solar Altivar 212 Altivar 71 Altivar 61Q Altivar 71Q
Accessory / separate part category	Display and signalling accessories
Accessory / separate part type	Display terminal
Accessory / separate part destination	Variable speed drive
Product Specific Application	To control, adjust and configure the drive To save and download configurations To display the current values
IP Degree of Protection	IP54

Complementary

Mounting Location	On the door of an enclosure
User Language	Italian English French Spanish German Chinese
Messages display capacity	8 lines
Pixel resolution	240 x 160
Net Weight	0.32 lb(US) (0.145 kg)

Environment

Ambient Air Temperature for Operation	5...122 °F (-15...50 °C)
---------------------------------------	--------------------------

Ordering and shipping details

Category	22135-ATV61-71 ACCESSORIES
Discount Schedule	CP4C
GTIN	3389118069305
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.76 in (7.000 cm)
Package 1 Width	6.50 in (16.500 cm)
Package 1 Length	9.06 in (23.000 cm)
Package 1 Weight	9.70 oz (275.000 g)

Unit Type of Package 2	P06
Number of Units in Package 2	56
Package 2 Height	30.31 in (77.000 cm)
Package 2 Width	31.50 in (80.000 cm)
Package 2 Length	23.62 in (60.000 cm)
Package 2 Weight	62.66 lb(US) (28.420 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------