



Hardwire Smoke Alarm with Front Load Battery Door

A premium choice for controlling false alarms.

Features:



• **Ionization Technology** – Better at detecting fast flaming fires.



• **120V AC Direct-Wire** – Interconnects with up to 24 units, of which 18 can be initiating.



• **9V Battery Backup (included)** – Continuous protection in case of power failure.



• **Test Button** – Tests circuitry and verifies alarm operation.



• **Hush® Button** – Quickly silences nuisance alarms.



• **Front Loading Battery Door** – Change the battery without removing the alarm.

• **Tamper Resistant** – Locks to inhibit tampering with the alarm, preventing the removal of batteries for continuous protection.

• **Low Battery Indicator** – Warning chirp sounds when battery needs replacement.



P1276CA



Specifications:

Product dimensions:	6" x 6" x 1.7" deep
Colour / Case Pack	White / 8 units
Electrical Rating:	120V AC, 60Hz, 80mA, 9V Battery Backup
Wiring:	Quick connect plug with 8" pigtails
Audio Alarm:	85dB
Temperature Range:	40°F (4.4°C) to 100°F (37.8°C)
Humidity Range:	Up to 85% relative humidity
Sensor:	Ionization
Limited Warranty:	5 Year
Weight:	0.70lb
UPC:	0-47871-27694-3

