



### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided equipment	CD with software Communication Cable Documentation CD Installation guide Removable support feet USB cable Warranty card
Product web sub-family	High density
Number of tare power	17 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	S

### Physical

Cable length	6 ft (1.83 m)
Color	Black
Depth	20.00 in (50.8 cm)
Height	17.01 in (43.2 cm)
Mounting position	Vertical
Mounting preference	No preference
Product Weight	48.50 lb(US) (22 kg)
Mounting Mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Width	3.35 in (8.5 cm)

### Input

Input Frequency	40 - 70 Hz auto-sensing
Plug standard	NEMA 5-15P
Efficiency at full load	108...150 V 50...150 V 40% load
Number of cables	1
Nominal Input Voltage	120 V

## Output

Kw Rating	1350 W
Max Configurable Power (Watts)	1350 W
Harmonic distortion	Less than 2%
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
Topology	Double Conversion Online
Waveform Type	Sine wave
Nb of power socket outlets	6 NEMA 5-15R
Bypass type	Built-in Bypass
Curve equation	Efficiency
Curve fixed loss	0.0255
Curve load maximum	100 %
Curve load minimum	3 %
Curve proportional loss	0.025
Curve square loss	0.0428
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data US DOE Test
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	120 V
Maximum configurable power in VA	1500 VA
Rated power in VA	1500 VA

## Conformance

Product Certifications	ENERGY STAR V2.0 (USA)
Standards	CSA C22.2 No.107.3-05 FCC Part 15 class A UL 1778

## Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-4...122 °F (-20...50 °C)
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	50 dBA
Heat dissipation	463 Btu/h
Show note OP temperature	No
IP degree of protection	IP20

## Batteries & Runtime

Battery Type	Lead-Acid battery
Included Battery Modules	1
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1

Liquid Electrolyte Value	0
Battery Voltage	48V
Battery curve	D
Battery Charge Power (Watts)	91 W rated
Battery power in VAH	273 VAh runtime
Battery life	3...5 year(s)
Battery option	SRT48BP 1 819 VAh SRT48BP 2 1365 VAh SRT48BP 3 1910 VAh SRT48BP 4 2456 VAh SRT48BP 5 3002 VAh SRT48BP 6 3548 VAh SRT48BP 8 4640 VAh SRT48BP 10 5731 VAh
Extendable Run Time	0

## Communications & Management

Free slots	1
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes

## Surge Protection and Filtering

Surge energy rating	432 J
---------------------	-------







## Ordering and shipping details

GTIN	00731304330097
Package weight(Lbs)	65.26 lb(US) (29.6 kg)

## Packing Units

Package 1 Height	9.69 in (24.6 cm)
Package 1 width	23.39 in (59.4 cm)
Package 1 Length	29.49 in (74.9 cm)
Number of Units in Package 3	12

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
Energy Star	 <a href="#">ENERGY STAR UPS V2.0 (USA)</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---