

AR3814

APC Netshelter AV, Server Rack Enclosure, 24U, 10-32 Threaded Rails, Black, 1199H x 600W x 806D mm



Overview

Presentation	Feature-rich enclosure specifically for the professional A/V market and optimized for cable management, power distribution, and airflow management.
Lead time	Usually in Stock

General

Provided equipment	Baying hardware Documentation CD Key(S) Keyed-alike doors and side panels Leveling feet Mounting Hardware Pre-installed casters Side Panels
--------------------	--

Physical

Maximum Mounting Depth	27.64 in (70.21 cm)
Number of rack unit	24U
Color	Black
Depth	32.48 in (82.5 cm)
Rack width	19"
Height	47.20 in (119.9 cm)
Product Weight	180.38 lb(US) (81.82 kg)
Permanent permissible load	2250 Lb(US) (1020.58 kg) dynamic 3000 lb(US) (1360.78 kg) static
Width	23.62 in (60 cm)

Conformance

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------

Ordering and shipping details

GTIN	00731304284109
Package weight(Lbs)	209.44 lb(US) (95 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Package 1 Height	52.24 in (132.7 cm)
Package 1 width	29.49 in (74.9 cm)
Package 1 Length	40.51 in (102.9 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Take-back	Take-back program available

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------