



GE  
Lighting

### 34418 - Integrated 2ft LED Glass Tubes T5 HO

#### LED11ET5/G/2/840

- ☞ Required T5 HO Ballast
- ☞ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall.
- ☞ Each LED tube is outfitted with an internal GE driver.
- ☞ The GE integrated LED tubes run on electronic T5 instant-start or programmed start ballasts.
- ☞ Longer life than LFL (50,000 vs. 30,000 hours)
- ☞ Easy disposal, non-hazardous waste
- ☞ UL Listed

#### Product Photo



#### GENERAL CHARACTERISTICS

Base Description	LED_Bs_G5
Base Type	G5
Dimmable	No
Product Technology	LED
Rated Life (Hours)	50000 h
Dimmable / Non-Dimmable	No

#### PHOTOMETRIC CHARACTERISTICS

Rated Beam Spread	11 W
-------------------	------

#### PRODUCT INFORMATION

Product Code	34418
Description	LED11ET5/G/2/840
Alternative Unit Of Measure	CASE
Standard Package Quantity	20
Ean UPC	043168344180
Standard Package GTIN	10043168344187
No Of Items Per Sales Unit	
No Of Items Per Standard Package	20
Sales Unit	Case
UCC	
Alternative Unit Of Measure	EACH
Standard Package Quantity	20
Ean UPC	043168344180
Standard Package GTIN	00043168344180
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
Sales Unit	Each
UCC	

#### DIMENSIONS

Bulb Max Overall Length-MOL	22.0 in
-----------------------------	---------