

# Product data sheet

Specifications



## Light Module, Harmony XVB7 Modular Tower Light, Red, Ø70mm, Blinking, Colored Lens

XVB7C54

### Main

|                           |                         |
|---------------------------|-------------------------|
| Range of product          | Harmony XVB7            |
| Product or component type | Light module            |
| Device composition        | Standard lens           |
| Device short name         | XVB7                    |
| Mounting diameter         | 2.8 in (70 mm)          |
| Signalling type           | Blinking                |
| Light color               | LED, red                |
| Material                  | PC (polycarbonate)      |
| Net weight                | 0.231 lb(US) (0.105 kg) |
| Mounting position         | Upright/inverted        |

### Complementary

|                                        |                                |
|----------------------------------------|--------------------------------|
| Blinking frequency                     | 1 Hz                           |
| Service life in hours                  | 50000 h                        |
| [Ue] rated operational voltage         | 24 V AC/DC                     |
| Rated operational voltage limits       | 21.6...26.4 V AC/DC            |
| Current consumption                    | 40 mA 24 V AC<br>45 mA 24 V DC |
| Inrush current                         | 0.5 A                          |
| Electrical shock protection class      | Class II                       |
| [Ui] rated insulation voltage          | 50 V                           |
| [Uimp] rated impulse withstand voltage | 0.5 kV                         |

### Environment

|                                       |                                          |
|---------------------------------------|------------------------------------------|
| Pollution degree                      | 2                                        |
| Ambient air temperature for operation | -13...140 °F (-25...60 °C)               |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)               |
| IP degree of protection               | IP66                                     |
| Environmental Type ratings            | UL type 4X/13                            |
| Vibration resistance                  | 6 gn +/- 0.5 mm 10...500 Hz)in operation |
| Shock resistance                      | 30 gn 6 ms) in operation                 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                        |                                                         |
|------------------------|---------------------------------------------------------|
| Standards              | UL 60947-5-1<br>IEC 60947-5-1<br>CSA C22.2 No 60947-5-1 |
| Product certifications | cULus<br>CCC<br>RCM<br>UKCA<br>CE                       |

## Packing Units

|                              |                          |
|------------------------------|--------------------------|
| Unit Type of Package 1       | PCE                      |
| Number of Units in Package 1 | 1                        |
| Package 1 Height             | 2.559 in (6.500 cm)      |
| Package 1 Width              | 2.874 in (7.300 cm)      |
| Package 1 Length             | 2.953 in (7.500 cm)      |
| Package 1 Weight             | 3.704 oz (105.000 g)     |
| Unit Type of Package 2       | S03                      |
| Number of Units in Package 2 | 60                       |
| Package 2 Height             | 11.8 in (30 cm)          |
| Package 2 Width              | 11.8 in (30 cm)          |
| Package 2 Length             | 15.7 in (40 cm)          |
| Package 2 Weight             | 14.941 lb(US) (6.777 kg) |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

|  Environmental footprint |                                               |
|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                                                                          | 13 kg CO2 eq.                                 |
| Carbon footprint of the manufacturing phase [A1 to A3]                                                    | 1 kg CO2 eq.                                  |
| Carbon footprint of the distribution phase [A4]                                                           | 0 kg CO2 eq.                                  |
| Carbon footprint of the installation phase [A5]                                                           | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]                                                        | 11 kg CO2 eq.                                 |
| Carbon footprint of the end-of-life phase [C1 to C4]                                                      | 0.1 kg CO2 eq.                                |
| Environmental Disclosure                                                                                  | <a href="#">Product Environmental Profile</a> |

### Use Better


|  Materials and Substances |                                                                                        |
|-------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard                                                                      | Yes                                                                                    |
| Packaging without single use plastic                                                                        | Yes                                                                                    |
| EU RoHS Directive                                                                                           | <a href="#">Compliant By Exemption</a>                                                 |
| REACH Regulation                                                                                            | <a href="#">Reference contains Substances of Very High Concern above the threshold</a> |

### Use Again

|  Repack and remanufacture |                                                                                                                                                                                                                 |
|--------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in %                                                                                | 87                                                                                                                                                                                                              |
| Circularity Profile                                                                                          | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| Take-back                                                                                                    | No                                                                                                                                                                                                              |
| WEEE Label                                                                                                   |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |


Dimensions Drawings

Dimensions



Mounting and Clearance

Mounting Overview



| Drawing | Part Number | Part Description |
|---------|-------------|------------------|
|---------|-------------|------------------|


|              |             |                                    |
|--------------|-------------|------------------------------------|
| A1, A6, A11  | XVB7C21B... | 24V Base Direct / Tube & Cover     |
| A1, A7, A11  | XVB7C31     | IO Link Base Direct / Tube & Cover |
| A1, A8, A11  | XVB7C51     | USB Base Direct / Tube & Cover     |
| A1, A9, A11  | XVB7C61     | M12 Base Direct / Tube & Cover     |
| A1, A10, A11 | XVB7C21M... | AC Base Direct / Tube & Cover      |
| A2           | XVB7C9S...  | 2 Tones Buzzer                     |
| A2           | XVB7C9T     | 8 Tones Buzzer                     |
| A2           | XVB7C9SS    | Self-Adjust Sounder 1 Tone         |
| A3           | XVB7L2...   | Beacon Steady Lens                 |
|              | XVB7L6...   | Beacon Flashing Lens               |
| A4           | XVB7C9V     | Editable Voice Alarm               |
| A5           | XVB7C2...   | Steady Lens                        |
|              | XVB7C5...   | Blinking Lens                      |
|              | XVB7C6...   | Flashing Lens                      |
|              | XVB7CR...   | Rotating Lens                      |
|              | XVB7CM9     | Multi-function Clear lens          |
| A12          | XVZ00       | 1/2" NPT Adapter                   |
| A13          | XVZ02...    | Plastic Fixing Plate With Pole     |
| A14          | XVZ100      | Alu Ø25mm Pole 100mm Length        |
| A15          | XVZ250      | Alu Ø25mm Pole 250mm Length        |
| A16          | XVZ400      | Alu Ø25mm Pole 400mm Length        |
| A17          | XVZ800      | Alu Ø25mm Pole 800mm Length        |
| A18          | XVZ100T     | L Bracket Alu Ø25mm Pole 100mm     |
| A19          | XVZ250T     | L Bracket Alu Ø25mm Pole 250mm     |
| A20          | XVZ01...    | Plastic Fixing Plate               |
| A21          | XVZ11       | Metal Fixing Plate                 |
| A22          | XVZ06...    | Plastic Foldable Bracket           |
| A23          | XVZ09       | Plastic Wall Mount Bracket         |

|     |       |                    |
|-----|-------|--------------------|
| A24 | XVZ07 | Side Entry Adapter |
| A25 | XVZ08 | Magnetic Adapter   |



Image of product / Alternate images

Alternative

---










Image of product in real life situation

