

Insulated Screwdrivers

FORGED STEEL

from Klein's US-made, proprietary blend

 **1000 V**

Klein insulated tools meet or exceed the IEC 60900 and ASTM F1505 standards, for insulated tools, and are clearly marked with the official 1000-volt rating symbol

Durable, two layer, molded insulation

Thick, exceptionally tough, high-dielectric white inner coating is bonded to the tool

Bright orange outer coating is flame and impact resistant

Cushion-Grip handles for greater torque and comfort

Tip-Ident® quickly identifies driver size

MADE IN USA

▲WARNING: Only use tools that are marked with the official international 1000-volt rating symbol shown below, if there is any chance that the tools will make contact with an energized source.

 **1000 V**

▲WARNING: Wear approved eye protection. Always inspect your tools before use. Do not use if orange coating cracks, breaks or becomes damaged. Destroy tool if white layer shows through orange layer.

Product numbers with the INS suffix contain these warnings and must be understood.

▲WARNING: Do NOT touch uninsulated portion of the tool or any conductive object when either might contact an energized source.

▲WARNING: Whenever possible, always de-energize lines and equipment prior to working on or around them. Klein insulated tools are designed only to reduce the chance of injury where the tool may make contact with an energized source.

▲WARNING: Because moisture, films, or other surface contaminants are conductive, Klein insulated tools must be kept clean, dry, and free of any surface contaminants.

Insulated Screwdrivers - Round-Shank

Additional Features:

- Profilated Phillips-tip provides a more consistent geometric symmetry than conventional Phillips-tip screwdrivers
- Square-Recess tips are perfect for electrical, telephone and work in recessed holes and other tight spaces



| Cat. No. | Tip Type | Tip Size | Shank Length | Overall Length | Weight |
|-----------|-------------|----------------|---------------|---------------------|--------------------|
| 6334INS | Phillips | #1 | 4" (101.6 mm) | 7-3/4" (196.9 mm) | 2.1 oz. (60 g) |
| 603-4-INS | Phillips | #2 | 4" (101.6 mm) | 8-5/16" (211.1 mm) | 3.2 lbs. (1.45 kg) |
| 6037INS | Phillips | #2 | 7" (177.8 mm) | 11-5/16" (287.3 mm) | 4.0 lbs. (1.81 kg) |
| 6337INS | Phillips | #1 | 7" (177.8 mm) | 12-3/8" (314.3 mm) | 6.4 lbs. (2.90 kg) |
| 607-3-INS | Cabinet Tip | 3/32" (2.4 mm) | 3" (76.2 mm) | 6-3/4" (171.5 mm) | 1.9 lbs. (0.86 kg) |
| 612-4-INS | Cabinet Tip | 1/8" (3.2 mm) | 4" (101.6 mm) | 7-3/4" (196.9 mm) | 2.1 oz. (60 g) |
| 601-4-INS | Cabinet Tip | 3/16" (4.8 mm) | 4" (101.6 mm) | 7-3/4" (196.9 mm) | 2.1 oz. (60 g) |
| 601-7-INS | Cabinet Tip | 3/16" (4.8 mm) | 7" (177.8 mm) | 10-3/4" (273.1 mm) | 2.7 lbs. (1.22 kg) |
| 602-4-INS | Cabinet Tip | 1/4" (6.4 mm) | 4" (101.6 mm) | 8-5/16" (211.1 mm) | 3.2 lbs. (1.45 kg) |
| 605-7-INS | Cabinet Tip | 1/4" (6.4 mm) | 7" (177.8 mm) | 11-5/16" (287.3 mm) | 4.0 lbs. (1.81 kg) |
| 602-7-INS | Cabinet Tip | 5/16" (7.9 mm) | 7" (177.8 mm) | 12-3/8" (314.3 mm) | 6.4 lbs. (2.90 kg) |
| 602-8-INS | Cabinet Tip | 3/8" (9.5 mm) | 8" (203.2 mm) | 13-3/8" (339.7 mm) | 8.0 oz. (227 g) |
| 661-4-INS | Square | #1 | 4" (101.6 mm) | 8-5/16" (211.1 mm) | 3.2 lbs. (1.45 kg) |
| 661-7-INS | Square | #1 | 7" (177.8 mm) | 11-5/16" (287.3 mm) | 3.2 lbs. (1.45 kg) |
| 662-4-INS | Square | #2 | 4" (101.6 mm) | 8-5/16" (211.1 mm) | 3.2 lbs. (1.45 kg) |
| 662-7-INS | Square | #2 | 7" (177.8 mm) | 11-5/16" (287.3 mm) | 3.2 lbs. (1.45 kg) |