



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided Equipment	User Manual USB cable
--------------------	--------------------------

Physical

Depth	4.49 in (11.4 cm)
Height	1.50 in (3.8 cm)
Product Weight	0.18 lb(US) (0.08 kg)
Width	4.76 in (12.1 cm)

Conformance

Standards	EN 55022 Class A EN 55024 ICES-003
Product Certifications	AS/NZS 3548 (C-Tick) Class A FCC part 15 class A GOST VCCI Class A

Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	23...113 °F (-5...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

Communications & Management

Authentication	Radius
----------------	--------

Ordering and shipping details

GTIN	00731304355533
Package weight(Lbs)	0.75 lb(US) (0.34 kg)

Packing Units

Package 1 Height	2.01 in (5.1 cm)
Package 1 width	9.25 in (23.5 cm)
Package 1 Length	6.26 in (15.9 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------