

KS39, Split Bolt Connector, Run/Tap: 4/0 AWG Str-750 kcmil

By Burndy
Catalog # [KS39](#)



Copper Split Bolt, Cu: 4/0 AWG (Str)-750 kcmil (Run & Tap).

Features

- UL467 Listed for Direct Burial applications in earth or concrete
- Compact, high-strength, copper alloy with free-running threads and easy to grip wrench flats
- Highly resistant to cracking and corrosion

Application

For Direct Burial Cables

General

Catalog Number	KS39
Connector Type	Split Bolt
EU RoHS Indicator	Yes
Installation Torque	1000 in
Recommended in-lb	
Material	Copper
Plated	N
Plating Type	Unplated
Sub Brand	SERVIT
Trade Name	SERVIT®
Type	KS
UPC	781810014752
UPC 12 Digit	7818100147522

Dimensions

Dimension - B Length inch	1.75 in
Dimension - Cross Flats inch	2.31 in
Dimension - L Length Overall mm	84 mm
Dimension - Length Overall inch	3.51
Dimension - Width inch	1.94 in
Dimension - Width mm	49 mm
Width	1.94 in

Conductor Related

Conductor - Copper Str Run	4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil;550 kcmil;600 kcmil;700 kcmil;750 kcmil
----------------------------	---

Conductor - Copper Str Run Range	4/0 STR - 750 KCMIL
Conductor - Copper Str Tap	4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil;550 kcmil;600 kcmil;700 kcmil;750 kcmil
Conductor - Copper Str Tap Range	4/0 STR - 750 KCMIL
Conductor - CopperWeld Str Run	19 #5
Conductor - CopperWeld Str Run Range	19 #5
Conductor - CopperWeld Str Tap	19 #5
Conductor - CopperWeld Str Tap Range	19 #5
Conductor Type	<ul style="list-style-type: none"> • CU C Str-Run • CU Weld C Str-Run • CU C Str-Tap • CU Weld C Str-Tap

Certifications And Compliance

Buy American Compliant	Contact Manufacturer
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes
Certification - UL Recognized	No
Certification - cULus	No
Certified Listed	BABA Compliant (All status valid till December 2024)
Industry Standard(s)	<ul style="list-style-type: none"> • UL 486A • UL486B
Standards - Industry Standards Met	<ul style="list-style-type: none"> • UL 486A • UL486B
Standards - RoHS Compliance Status	EX
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[3D Models - KS39_MODEL-PDF](#)

3D Models - KS39_MODEL-IGES
3D Models - KS39_MODEL-STEP
Catalogs - BURNDY Master Catalog - Section A - Mechanical
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_KS_Lineart_BW
Sales Drawings - SD..078561-01
Sell Sheets - SERVIT® Split-bolt Connectors
Specifications - KS39



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
BRDY-KS39-SPEC-EN | REV 1/2025