


TYPE

GT

Made from high copper content alloy. Furnished with silicon bronze bolt, nuts and lockwashers.

For clamping parallel cables or wires to pipe or rod



Catalog Number	Accommodates		Conductor Range	Wire Diameter Range in	Approximate Dimensions								Bolt Dia.†
	Rod	IPS			A		B		C		D		
					in	mm	in	mm	in	mm	in	mm	
GT-1	1/2	1/4	8 Sol.-4 Str.	.128- .232	1 5/8	41	2	51	1 5/8	41	1	25	3/8
GT-2	1/2	1/4	4 Sol.-2/0 Str.	.204- .419	2	51	2 1/8	54	1 3/4	44	1	25	3/8
GT-3	1/2	1/4	2/0 Sol.-250 MCM	.365- .575	2 1/2	64	2 1/4	57	1 7/8	47	1	25	3/8
GT-4	5/8 or 3/4	3/8	8 Sol.-4 Str.	.128- .232	1 5/8	41	2 1/8	54	1 5/8	41	1 1/8	28	3/8
GT-5	5/8 or 3/4	3/8	4 Sol.-2/0 Str.	.204- .419	2	51	2 1/2	64	1 3/4	44	1 1/8	28	3/8
GT-6	5/8 or 3/4	3/8	2/0 Sol.-250 MCM	.365- .575	2 1/2	64	2 3/8	67	1 7/8	47	1 1/8	28	3/8
GT-7	5/8 or 3/4	3/8	300-500 MCM	.634- .815	2 3/4	70	2 3/4	70	2	51	1 1/8	28	3/8
GT-8	7/8 or 1	1/2 or 3/4	8 Sol.-4 Str.	.128- .232	1 5/8	41	2 1/2	64	1 5/8	41	1 1/2	38	3/8
GT-9	7/8 or 1	1/2 or 3/4	4 Sol.-2/0 Str.	.204- .419	2	51	2 3/4	70	1 3/4	44	1 1/2	38	3/8
GT-10	7/8 or 1	1/2 or 3/4	2/0 Sol.-250 MCM	.365- .575	2 1/2	64	2 7/8	73	1 7/8	47	1 1/2	38	3/8
GT-11	7/8 or 1	1/2 or 3/4	300-500 MCM	.634- .815	2 3/4	70	3	76	2	51	1 1/2	38	3/8
GT-12	7/8 or 1	1/2 or 3/4	500-750 MCM	.815- .999	3 1/8	79	3 3/4	95	2 1/4	57	1 5/8	41	1/2
GT-13	-	1	8 Sol.-4 Str.	.128- .232	1 5/8	41	2 3/4	70	1 5/8	41	1 3/4	44	3/8
GT-14	-	1	4 Sol.-2/0 Str.	.204- .419	2	51	3	76	1 3/4	44	1 3/4	44	3/8
GT-15	-	1	2/0 Sol.-250 MCM	.365- .575	2 1/2	64	3 7/8	98	3 3/8	79	1 3/4	44	3/8
GT-16	-	1	300-500 MCM	.634- .815	2 3/4	70	3 3/4	95	2	51	1 3/4	44	3/8
GT-17	-	1	500-750 MCM	.815- .999	3 1/8	79	4 1/8	105	2 1/4	57	1 7/8	47	1/2
GT-18	-	1 1/4	8 Sol.-4 Str.	.128- .232	1 5/8	41	3	76	1 7/8	47	2 1/16	53	3/8
GT-19	-	1 1/4	4 Sol.-2/0 Str.	.204- .419	2	51	3 1/4	82	2	51	2 1/16	53	3/8
GT-20	-	1 1/4	2/0 Sol.-250 MCM	.365- .575	2 1/2	64	3 1/2	89	2 1/8	54	2 1/16	53	3/8
GT-21	-	1 1/4	300-500 MCM	.634- .815	2 3/4	70	4 1/8	105	2 1/4	57	2 3/16	56	1/2
GT-22	-	1 1/4	500-750 MCM	.815- .999	3 3/4	95	4 3/8	111	2 1/2	64	2 5/16	59	5/8
GT-23	-	1 1/4	750-1000 MCM	.999-1.153	4	102	4 5/8	118	2 3/4	70	2 5/16	59	5/8
GT-24	-	1 1/2	8 Sol.-4 Str.	.128- .232	1 5/8	41	3 1/4	82	2 1/4	57	2 3/8	60	3/8
GT-25	-	1 1/2	4 Sol.-2/0 Str.	.204- .419	2	51	3 1/2	89	2 3/8	60	2 3/8	60	3/8
GT-26	-	1 1/2	2/0 Sol.-250 MCM	.365- .575	2 1/2	64	3 7/8	98	2 1/2	64	2 3/8	60	3/8
GT-27	-	1 1/2	300-500 MCM	.634- .815	2 3/4	70	4 3/8	111	2 5/8	67	2 1/2	64	1/2
GT-28	-	1 1/2	500-750 MCM	.815- .999	3 3/4	95	4 3/4	121	2 3/4	70	2 5/8	67	5/8
GT-29	-	1 1/2	750-1000 MCM	.999-1.153	4	102	5	127	2 7/8	73	2 5/8	67	5/8
GT-30	-	2	8 Sol.-4 Str.	.128- .282	1 3/4	44	3 7/8	98	2 3/4	70	2 13/16	71	3/8
GT-31	-	2	4 Sol. 2/0 Str.	.204- .419	2	51	4 1/8	105	2 7/8	73	2 13/16	71	3/8
GT-32	-	2	2/0 Sol.-250 MCM	.365- .575	2 5/8	67	4 1/4	108	3	76	2 13/16	71	3/8
GT-33	-	2	300-500 MCM	.634- .815	2 7/8	73	4 5/8	118	3 1/8	79	2 15/16	75	1/2
GT-34	-	2	500-750 MCM	.815- .999	3 3/4	95	5 1/4	133	3 1/4	82	3 1/16	78	5/8
GT-35	-	2	750-1000 MCM	.999-1.153	4	102	5 1/2	140	3 1/4	82	3 1/16	78	5/8
GT-36	-	2 1/2	8 Sol.-4 Str.	.128- .232	1 3/4	44	4 3/8	111	3 3/8	85	3 5/8	92	3/8
GT-37	-	2 1/2	4 Sol.-2/0 Str.	.204- .419	2	51	4 1/2	115	3 3/8	85	3 5/16	84	3/8
GT-38	-	2 1/2	2/0 Sol.-250 MCM	.365- .575	2 5/8	67	4 3/4	121	3 1/2	89	3 3/16	84	3/8
GT-39	-	2 1/2	300-500 MCM	.634- .815	2 7/8	73	5 1/8	130	3 5/8	92	3 7/16	87	1/2
GT-40	-	2 1/2	500-750 MCM	.815- .999	3 3/4	95	5 5/8	143	3 3/4	95	3 3/16	90	5/8
GT-41	-	2 1/2	750-1000 MCM	.999-1.153	4	102	5 3/4	146	3 3/4	95	3 9/16	90	5/8
GT-42	-	3	8 Sol.-4 Str.	.128- .232	1 3/4	44	5	127	3 5/8	92	3 15/16	100	3/8
GT-43	-	3	4 Sol.-2/0 Str.	.204- .419	2	51	5 1/4	133	3 3/4	95	3 15/16	100	3/8
GT-44	-	3	2/0 Sol.-250 MCM	.365- .575	2 5/8	67	5 1/2	140	3 3/4	95	3 15/16	100	3/8
GT-45	-	3	300-500 MCM	.634- .815	2 7/8	73	5 7/8	149	3 7/8	98	4 1/16	104	1/2
GT-46	-	3	500-750 MCM	.815- .999	3 3/4	95	6 1/2	165	4 1/8	105	4 3/16	107	5/8
GT-47	-	3	750-1000 MCM	.999-1.153	4	102	6 3/4	171	4 1/8	105	4 3/16	107	5/8
GT-48	-	3 1/2	8 Sol.-4 Str.	.128- .232	1 3/4	44	5 1/2	140	3 7/8	98	4 7/16	113	3/8
GT-49	-	3 1/2	4 Sol.-2/0 Str.	.204- .419	2	51	5 7/8	149	3 7/8	98	4 7/16	113	3/8
GT-50	-	3 1/2	2/0 Sol.-250 MCM	.365- .575	2 5/8	67	6 1/8	155	4	102	4 7/16	113	3/8
GT-51	-	3 1/2	300-500 MCM	.634- .815	2 7/8	73	6 1/2	165	4 1/4	105	4 9/16	116	1/2
GT-52	-	3 1/2	500-750 MCM	.815- .999	3 3/4	95	7 1/8	181	4 5/8	118	4 11/16	119	5/8
GT-53	-	3 1/2	750-1000 MCM	.999-1.153	4	102	7 3/8	187	4 5/8	118	4 11/16	119	5/8
GT-54	-	3 1/2	1250-1500 MCM	1.290-1.412	4 1/4	108	7 5/8	194	4 3/4	121	4 11/16	119	5/8
GT-55	-	4	2/0 Sol.-250 MCM	.365- .575	2 5/8	67	6 1/2	165	4 3/4	121	4 15/16	126	3/8
GT-56	-	4	300-500 MCM	.634- .815	2 7/8	73	7	178	5	127	5 1/16	129	1/2

† 3/8" U-Bolt threaded as shown above, add suffix "FT" for full thread. 1/2" U-Bolt standard is full thread.