



GE
Lighting

63098 - High frequency electronic ballasts for 2 or 1 CFL lamps

GEC226-MVPS-BES

- ☞ Line Voltage: Multi-Voltage 120 to 277 VAC, +/-10%, 50-60Hz
- ☞ Series Lamp Operation
- ☞ IC Control
- ☞ Programmed starting for extended lamp life
- ☞ Active Power Factor Correction

GENERAL CHARACTERISTICS

Ambient Temp [Max]	40 °C
Ambient Temp [Min]	-29 °C
Ballast Factor	High (1.15)
Ballast Type	High Frequency Electronic Ballasts
Enclosure Type	Metal Can
Line Voltage Regulation (+/-)	10
Classification (Regulations)	ANSI - C62.41 ANSI - C82.11 FCC Part 18 Class B at 120 volts No PCB's UL Listed UL Class P UL Type 1 Outdoor cUL Listed
Sound Rating	A (20-24 decibels)
Starting Method	Programmed start
Product Technology	Compact Fluorescent
Lamp Wiring	Series
Power Factor Correction	Active

PRODUCT INFORMATION

Product Code	63098
Description	GEC226-MVPS-BES
Alternative Unit Of Measure	03-Master
Standard Package Quantity	10
Ean UPC	043168630986
Standard Package GTIN	10043168630983
No Of Items Per Sales Unit	10
No Of Items Per Standard Package	10
Sales Unit	Pallet
UCC	043168630986

DIMENSIONS

Weight	0.46 lb
Exit Type	Side

Case Dimensions

Length	4.25in
Width	2.31in
Height	1.0in

Mounting Dimensions

Mount Length	4.61in
Mount Width	0.98in
Mount Offset	1.0in

SAFETY & PERFORMANCE

- ☞ ANSI_C62
- ☞ ANSI_C82
- ☞ FCC_Part_18
- ☞ No_PCB
- ☞ UL_Listed
- ☞ UL_Cls_P
- ☞ UL_Type1_Out
- ☞ cUL_Listed

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F/ C)
FT24W/2G1 1	1	277	27	0.11	1.1		0.91	1.7	14	-20
FT24W/2G1 1	1	120	27	0.23	1.04		0.99	1.7	10	-20

FT36W/2G1 1	1	277	35	0.13	0.94		0.94	1.7	13	-20
FT36W/2G1 1	1	120	35	0.29	0.94		0.99	1.7	10	-20
CFQ26W	1	120	30	0.25	1.04		0.99	1.7	10	-20
CFQ26W	1	277	30	0.12	1.04		0.93	1.7	13	-20
CFTR26W	1	120	32	0.26	1.01		0.99	1.7	10	-20
CFTR26W	1	277	32	0.12	1.0		0.94	1.7	13	-20
CFTR26W	2	120	64	0.53	0.97		0.99	1.7	10	-20
CFTR26W	2	277	64	0.23	0.88		0.97	1.7	12	-20
CFS21W	2	277	55	0.2	1.11		0.96	1.7	11	-20
CFS21W	2	120	56	0.47	1.12		0.99	1.7	10	-20
CFQ26W	2	277	54	0.2	1.02		0.97	1.7	11	-20
CFQ26W	2	120	56	0.47	1.02		0.99	1.7	10	-20
CFTR42W	1	120	51	0.42	0.92		0.99	1.7	10	-20
CFTR42W	1	277	50	0.18	0.92		0.97	1.7	12	-20
FC16T9	1	277	40	0.14	0.94		0.95	1.7	13	-20
FC16T9	1	120	40	0.34	0.89		0.99	1.7	10	-20
CFTR32W/G X24q	1	120	39	0.33	1.24		0.99	1.7	10	
CFTR32W/G X24q	1	277	39	0.15	1.23		0.95	1.7	13	-20
FT39W/2G1 1	1	120	33	0.27	0.97		0.99	1.7	10	-20
FT39W/2G1 1	1	277	33	0.12	0.98		0.94	1.7	14	-20

