



PRODUCT SEARCH

[> SUPP](#)
[> DIST](#)
[HOME](#)[WHAT'S NEW](#)[SERVICE / SUPPORT](#)[WHERE TO BUY](#)[INSTRUCTION MANUALS](#)[CO](#)**Navigation**[Hand Tools](#)[Holemaking](#)[Bending](#)[Fishing](#)[Cable Pulling](#)[Wire & Cable Termination](#)[Voice Data Video](#)[Testing & Measurement](#)[Storage & Material Handling](#)[Hydraulic Pumps & Miscellaneous](#)**Name:**

Draw Stud - 3/4" x 4-3/4"

Cat #:

12099

UPC #:

12099

Spec:

SPECIFICATIONS Maximum Cutting Depth 8 Ga. (4 mm)

Description:

Time saving ball bearing head punches faster than wrench method.

- Requires less than half the force of conventional ratchet drivers.
- Punches up through 10 gauge (3.5 mm) mild steel with Greenlee Standard and Slug-Buster® punches; and 16 gauge (1.5 mm) stainless steel with Greenlee Slug-Splitter® punches.
- Ratchet action allows for use in confined areas.
- Unique design eliminates stud rotation during punching -
- lowers the strain on studs.
- Steel carrying case.

© 2007 Greenlee Textron Inc., a subsidiary of [Textron Inc.](#) All rights reserved.
[Privacy Policy](#) [Terms of Use](#) [Careers](#)