

TX6A™ U/UTP Copper Cable Standard Compliant Plus

SPECIFICATIONS

Category 6A/Class E_A cable shall be constructed of 23 AWG copper conductors with FEP insulation. The copper conductors shall be twisted in pairs. All four pairs shall be surrounded by a non-conductive AXT barrier tape and a flame retardant jacket. The AXT barrier tape shall minimize the cable diameter and suppress the effects of alien crosstalk. The small cable diameter shall maximize cable density such that existing pathways can be utilized when upgrading from Category 6 cabling.



TX6A™ U/UTP Copper Cable: Standard Compliant Plus

CMP: PUP6XHD04**G

****Colors:** BU (Blue), WH (White), RD (Red), OR (Orange), YL (Yellow), GR (Green), VL (Violet), IG (International Gray), or BL (Black)
For additional cable colors, contact customer service.

TECHNICAL INFORMATION

| | |
|--|--|
| Category 6A/Class EA channel and component performance: | Certified channel performance in a 4-connector configuration up to 100m and exceeds the requirements of ANSI/TIA-568.2-E Category 6A and ISO 11801 Class E _A standards swept up to 650 MHz for supporting 10GBASE-T transmission over twisted-pair cabling systems as part of the Panduit® TX6A™ U/UTP Copper Cabling System Certified component performance up to 100m and exceeds the ANSI/TIA-568.2-E Category 6A and IEC 61156-5 Category 6A standards for supporting 10GBASE-T transmission over twisted-pair cabling systems |
| Standards compliance: | UL Listed CMP-LP (0.7A) |
| Cable diameter: | 0.230 in. (5.8mm) nominal |
| Insulation diameter: | 0.039 in- 0.047 in (0.99mm - 1.19mm) |
| Conductors/insulators: | 23 AWG solid copper insulated with FEP |
| Flame rating: | NFPA 262 |
| PoE compliant: | Meets IEEE 802.3af, IEEE 802.3at and IEEE 802.3bt for PoE applications |
| Installation tension: | 25 lbf (110 N) maximum |
| Temperature rating: | 32°F to 140°F (0°C to 60°C) during installation -4°F to 221°F (-20°C to 105°C) during operation |
| Cable jacket: | Flame retardant (CMP) |
| Cable weight: | 30 lbs./1000 ft. (14 kg/305m) |
| Temperature rating: | 32°F to 122°F (0°C to 50°C) during installation -40°F to 167°F (-40°C to 75°C) during operation |
| Packaging: | 1000 ft. (305m) on a reel Package tested to ISTA Procedure 1A |

KEY FEATURES AND BENEFITS

| | |
|---|--|
| High density cable design | Improves fill capacity, cable management, reduces required bend radius and allows efficient use of pathways and spaces |
| Extended temperature range | Allows operation in 105°C (221°F) ambient environment providing error-free performance in high-density cabinets and large cable bundles running PoE+ or PoE++ applications |
| Highest port density | All testing and headroom based on 48-port/1RU panels |
| Descending length cable markings | Easy identification of remaining cable to reduce installation time and cable scrap |

TX6A™ U/UTP Copper Cable Standard Compliant Plus

APPLICATIONS

The TX6A™ U/UTP Copper Cable is a component of the TX6A™ Copper Cabling System. Interoperable and backward compatible, this end-to-end system provides design flexibility to protect network investments well into the future.

Key applications include:

- 10GBASE-T Ethernet
- Data center I/O consolidation
- Data center server virtualization
- Consolidation of network interconnects
- Back-bone aggregation
- Parallel processing and high speed computing

ADDITIONAL SPECIFICATIONS

| Mechanical Test | |
|--|--------------------|
| Ultimate breaking strength: | > 90 lbf (400 N) |
| Minimum bend radius: | 4 x cable diameter |
| Electrical Test | |
| Nominal velocity of propagation (NVP): | 70% nominal |
| Operating voltage, maximum: | 80 V |

ENGINEERING DRAWING

