



GE
Lighting

19348 - Integrated 4ft

LED26ET5/G/4/850

- ☞ Required T5 HO Ballast
- ☞ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall.
- ☞ Each LED tube is outfitted with an internal GE driver.
- ☞ The GE integrated LED tubes run on electronic T5 instant-start or programmed start ballasts.
- ☞ Longer life than LFL (50,000 vs. 30,000 hours)
- ☞ Easy disposal, non-hazardous waste
- ☞ UL Listed

Product Photo



GENERAL CHARACTERISTICS

Base Description	LED_Bs_G5
Base Type	G5
Product Technology	LED
Rated Life (Hours)	50000 h
LED Tube Type	Glass
Environmental Rating	LED_Tube_Glass

PHOTOMETRIC CHARACTERISTICS

Initial Lumens-nominal	3900 lm
Color Rendering Index-CRI	80
Color Temperature	5000 K

PRODUCT INFORMATION

Product Code	19348
Description	LED26ET5/G/4/850
Alternative Unit Of Measure	EACH
Standard Package Quantity	20
Ean UPC	043168193481
Standard Package GTIN	00043168193481
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
Sales Unit	Each
UCC	
Alternative Unit Of Measure	CASE
Standard Package Quantity	20
Ean UPC	043168193481
Standard Package GTIN	10043168193488
No Of Items Per Sales Unit	
No Of Items Per Standard Package	20
Sales Unit	Case
UCC	

DIMENSIONS

Bulb Max Overall Length-MOL	48.0 in
-----------------------------	---------

ELECTRICAL CHARACTERISTICS

Rated power (Watts)	25 W
---------------------	------