



Main

Range of product	OsiSense XC
Product or component type	Limit switch contact block
Device short name	XE2S
Electrical connection	Screw-clamp terminals 1 x 0.34...2 x 1.5 mm ²
Number of poles	2
Contacts type and composition	1 NO + 1 NC
Contacts operation	Snap action, break before make
Positive opening	With

Complementary

Product compatibility	XCKD XCKJ XCKL XCKM XCKP XCKS XCR
Associated body	ZCD21 ZCKJ1 ZCKJ1D ZCKL1 ZCKM1 ZCKS1 ZCP21
Contacts insulation form	Zb
Contacts material	Silver plated contacts
Minimum actuation speed	0,01 mm/s
Contact code designation	A300 AC-15 240 V 3 A 10 A EN/IEC 60947-5-1 appendix A Q300 DC-13 250 V 0,27 A EN/IEC 60947-5-1 appendix A
Resistance across terminals	< 25 mOhm IEC 60255-7 category 3
[Ui] rated insulation voltage	300 V UL 508 300 V CSA C22-2 No 14 500 V 3 IEC 60947-1
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-1 6 kV IEC 60664
Short circuit protection	10 A cartridge fuse gG
Electrical durability	5000000 cycles DC-13 24 V 10 W IEC 60947-5-1 appendix C < 60 cyc/mn 0,5 5000000 cycles DC-13 48 V 7 W IEC 60947-5-1 appendix C < 60 cyc/mn 0,5 5000000 cycles DC-13 120 V 4 W IEC 60947-5-1 appendix C < 60 cyc/mn 0,5
Environment	
RoHS EUR conformity date	0843
RoHS EUR status	Compliant