


STANDARD SUPPORT GRIPS



Remke Support Grips are designed to sustain and shore up the weight of cable in vertical or sloping applications. Constructed of on-magnetic tin-bronze wire, they assist in absorbing strain and flexure; and resist pullout, flexure and vibration. Standard Support Grips are available in a wide selection of eye styles and cable ranges. They will support cable rods and tubing with loads up to 600 lbs. Not recommended for runs over 100 feet.



Double Eye



Single Eye



Offset Eye



Universal Bail

Cable Range	Part #	Description	Approx.* Breaking Strength	Length	
				Eye	Mesh
Closed Mesh - Double Eye - Single Weave					
.50-.62	2201-001	R050-DE	530	4	10
.63-.74	2201-002	R062-DE	790	4	10
.75-.99	2201-003	R075-DE	1020	4	13
1.00-1.24	2201-004	R100-DE	1610	5	14
1.25-1.49	2201-005	R125-DE	1610	5	15
1.50-1.74	2201-006	R150-DE	1610	5	17
1.75-1.99	2201-007	R175-DE	2150	6	19
2.00-2.49	2201-008	R200-DE	3260	6	21
2.50-2.99	2201-009	R250-DE	3260	6	23
3.00-3.49	2201-010	R300-DE	4900	8	25
3.50-3.99	2201-011	R350-DE	4900	8	27

Cable Range	Part #	Description	Approx.* Breaking Strength	Length	
				Eye	Mesh
Closed Mesh - Single Eye - Single Weave					
.50-.62	2201-013	R050-SE	530	7	10
.63-.74	2201-014	R062-SE	790	8	10
.75-.99	2201-015	R075-SE	1020	8	13
1.00-1.24	2201-016	R100-SE	1610	9	14
1.25-1.49	2201-017	R125-SE	1610	10	15
1.50-1.74	2201-018	R150-SE	1610	12	17
1.75-1.99	2201-019	R175-SE	2150	14	19
2.00-2.49	2201-020	R200-SE	3260	16	21
2.50-2.99	2201-021	R250-SE	3260	18	23
3.00-3.49	2201-022	R300-SE	4900	21	25
3.50-3.99	2201-023	R350-SE	4900	24	27

Cable Range	Part #	Description	Approx.* Breaking Strength	Length	
				Eye	Mesh
Closed Mesh - Offset Eye - Single Weave					
.50-.62	2201-025	R050-OFS	500	4	10
.63-.74	2201-026	R062-OFS	750	4	10
.75-.99	2201-027	R075-OFS	950	4	13
1.00-1.24	2201-028	R100-OFS	1500	5	14
1.25-1.49	2201-029	R125-OFS	1500	5	15
1.50-1.74	2201-030	R150-OFS	1500	5	17
1.75-1.99	2201-031	R175-OFS	2000	6	19
2.00-2.49	2201-032	R200-OFS	3100	6	21
2.50-2.99	2201-033	R250-OFS	3100	6	23
3.00-3.49	2201-034	R300-OFS	3800	9	25
3.50-3.99	2201-035	R350-OFS	3800	9	27

Cable Range	Part #	Description	Approx.* Breaking Strength	Length	
				Eye	Mesh
Closed Mesh - Universal Bail - Single Weave					
.50-.62	2201-037	R050UB-18"	530	18	10
.63-.74	2201-038	R062UB-18"	790	18	10
.75-.99	2201-039	R075UB-18"	1020	18	13
1.00-1.24	2201-040	R100UB-18"	1610	18	14
1.25-1.49	2201-041	R125UB-18"	1610	18	15
1.50-1.74	2201-042	R150UB-18"	1610	18	17
1.75-1.99	2201-043	R175UB-18"	2150	18	19
2.00-2.49	2201-044	R200UB-18"	3260	18	21
2.50-2.99	2201-045	R250UB-18"	3260	18	23
3.00-3.49	2201-046	R300UB-18"	4900	18	25
3.50-3.99	2201-047	R350UB-18"	4900	18	27

All mesh is available as double weave or stainless steel. Consult factory for availability.

