

Eaton AHMC240C-3

Catalog Number: AHMC240C-3

Eaton manual motor controller, #14-8 AWG, 40A, Panel, 600V, Side wired screw and clamp, Maintained contact, Gray, NEMA 3R,; Copperless aluminum, Two-pole, Single-phase, Toggle, Copper-alloy terminal, Single-throw, Glass-filled nylon



Photo is representative

General specifications

Product Name	Catalog Number
Eaton manual motor controller	AHMC240C-3
UPC	Product Length/Depth
040893662664	6.22 in
Product Height	Product Width
5.47 in	5.44 in
Product Weight	Compliances
3.05 lb	NAFTA
	RoHS Compliant
Certifications	
cULus Listed	

defaultTaxonomyAttributeLabel

Enclosure

NEMA 3R

Type

Manual motor controller

Amperage Rating

40A

Voltage rating

600 V

Number Of Poles

Two-pole

Phase

Single-phase

Enclosure material

Copperless aluminum

Application

Industrial

Device grade

Industrial

Wiring method

Side wired screw and clamp

Contact type

Maintained

NEMA Rating

3R

Switch type

Toggle switch

Mounting method

Panel

Closure type

Maintained

Number of positions

2

Allowable wire size

#14-8 AWG

Resources

Catalogs

[Arrow Hart Buyers Guide Section E](#)

Specifications and datasheets

[Eaton Specification Sheet - AHMC240C-3](#)

Material

Glass-filled nylon

Termination style

Side wired screw and clamp

Throw

Single-throw

Terminals

Copper-alloy, brass screw

Color

Gray



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)