

# Product data sheet

## Characteristics

# 8910DPA52V02

Contactor, Definite Purpose, 50A, 2 pole, 10HP at 230VAC, 1 phase, 110/120VAC 50/60Hz coil, open



### Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	50 A
Number of Poles	2P
Pole contact composition	2 NO
Range of Product	DPA

### Complementary

Maximum Horse Power Rating	3 Hp 115 V AC, 1 phase 10 hp 230 V AC, 1 phase
Locked rotor rated current	300 A 277 V AC 250 A 460 V AC 200 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	1 phase
Electrical Connection	Quick connect terminals Box lugs

### Environment

Product Certifications	UL Recognized[RETURN]CSA
------------------------	--------------------------

### Ordering and shipping details

Category	21345-8910 DPA 5_(50 AMP)
Discount Schedule	CP1B
GTIN	785901080763
Returnability	Yes
Country of origin	CN

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.80 in (9.652 cm)
Package 1 Width	4.30 in (10.922 cm)
Package 1 Length	2.70 in (6.858 cm)
Package 1 Weight	23.04 oz (653.173 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	8.20 in (20.828 cm)
Package 2 Width	5.50 in (13.97 cm)

Package 2 Length	8.90 in (22.606 cm)
Package 2 Weight	11.83 lb(US) (5.366 kg)

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions

