

K11A39U2, Aluminum Universal Terminal, 2 Hole, Two: 1/0 AWG (Str)-750 kcmil, 3/8" Stud, 1.38" Stud Hole Spacing, 2 Screws, Al/Cu Rated, Tin Plated.



By Burndy
Catalog # [K11A39U2](#)

Aluminum Universal Terminal, 2 Hole, Two: 1/0 AWG (Str)-750 kcmil, 3/8" Stud, 1.38" Stud Hole Spacing, 2 Screws, Al/Cu Rated, Tin Plated.

Features

- Constructed from high strength, extruded aluminum alloy
- Electro tin-plated to provide low contact resistance

Application

For Aluminum and Copper Conductors

General

| | |
|--------------------------------------|-------------------------|
| Catalog Number | K11A39U2 |
| Connector Type | Stacked |
| EU RoHS Indicator | No |
| Hex Key | 3/8 |
| Installation Torque | 375 LBS/in |
| Recommended in-lb | |
| Material | Aluminum |
| Material - Hardware | Aluminum |
| Physical Attribute - Number of Holes | 2 |
| Physical Attribute - Screw Type | Allen |
| Plated | Y |
| Plating Type | Tin plated |
| Sub Brand | UNIVERSAL TERM |
| Temperature Rating | 194 |
| Type | Bolted Lugs & Terminals |
| UPC | 781810370292 |
| UPC 12 Digit | 7818103702922 |

Dimensions

| | |
|---------------------------------|---------|
| Dimension - Bolt Hole Size inch | 0.38 in |
| Dimension - Bolt Size fraction | 3/8 |
| Dimension - D inch | 2.31 in |
| Dimension - Height fraction | 3 in |
| Dimension - Height inch | 3.02 in |
| Dimension - Height mm | 76.7 mm |
| Dimension - Hole Size inch | 0.41 in |
| Dimension - Hole Size mm | 10 mm |

| | |
|---------------------------------|-------------|
| Dimension - L Length Overall mm | 125 mm |
| Dimension - Length Overall inch | 4.91 in |
| Dimension - N inch | 0.38 in |
| Dimension - Pad Width inch | 1.52 in |
| Dimension - Screw Size inch | 13/16 |
| Dimension - Stud Size fraction | 3/8 |
| Dimension - Stud Size inch | 3/8 in |
| Dimension - Width fraction | 1-69/100 in |
| Dimension - Width inch | 1.52 in |
| Dimension - Width mm | 43 mm |

Electrical Ratings

| | |
|--------------------------|-----|
| Rating - Minimum Voltage | 600 |
|--------------------------|-----|

Conductor Related

| | |
|-------------------------------------|---|
| Conductor - AL Str Size | 1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;266 kcmil;300 kcmil;336 kcmil;350 kcmil;397 kcmil;400 kcmil;450 kcmil;477 kcmil;500 kcmil;550 kcmil;556 kcmil;600 kcmil;636 kcmil;650 kcmil;700 kcmil;715 kcmil;750 kcmil |
| Conductor - AL Str Size Range | 1/0 AWG (Str)-750 kcmil |
| Conductor - Copper Solid Size | 1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG |
| Conductor - Copper Solid Size Range | 1/0 AWG-4/0 AWG |
| Conductor - Copper Str Size | 1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil;550 kcmil;600 kcmil;700 kcmil;750 kcmil |
| Conductor - Copper Str Size Range | 1/0 AWG (Str)-750 kcmil |
| Conductor Size | 1/0 AWG-750 KCMIL |

Conductor Type

- AL C Str-Size
- CU C Str-Size
- CU C Solid-Size

Number of Conductors 2

UL Listed Yes

Logistics

Minimum Pack Quantity 1

Certifications And Compliance

Buy America(n) Qualified Buy American Act Compliant (All status valid till December 2024)

Buy American Compliant Yes

Certification - CSA Approved Yes

Certification - UL Listed Direct No

Burial

Industry Standard(s) UL 486A-486B

Standards - Industry Standards Met UL 486A-486B

Standards - RoHS Compliance Status NC

Product Assets

[3D Models - K11A39U2_MODEL-STEP](#)

[3D Models - K11A39U2_MODEL-PDF](#)

[3D Models - K11A39U2_MODEL-IGES](#)

[Catalogs - BURNDY Master Catalog - Section A - Mechanical](#)

[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)

[Customer Notices - Prop 65 Notice](#)

[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)

[Product Cross Section Image\(s\) - BUR_K22AU_Lineart](#)

[Sales Drawings - se210997](#)

[Specifications - K11A39U2](#)

