

ALUMINUM PRE-INSULATED PENN-SLEEVES

• TYPE PIK

For aluminum to copper or aluminum to aluminum





Pre-insulated Penn-Sleeve Service Entrance Compression Connectors feature extra length for increased contact and solid center barrier.

Pre-filled with Cual-Aid inhibitor and capped to prevent dirt from accumulating in barrel and seal out moisture. Brilliant colour of caps for easy identification conform to industry standards, and easy push-thru caps reduce push thru force by 25%.

Aluminum insert is anchored to jacket, assuring that insert is under die when crimping where marking indicates. Strip gage and number of crimps marked on jacket make it hard to misapply. Conforms to ANSI C 119.4 when properly installed.

Nylon jacket insulates connector electrically and protects against water and weather. Special nylon formulated for Penn-Union increases shelf life and improves crimpability even at sub zero temperatures.



F

Part #	A Range			Wire Diameter Range in	Cap Colour	B Range			Wire Diameter Range in	Cap Colour	Die Size
	ACSR	Alum. or Copper				ACSR	Alum. or Copper				
		Str.	Sol.			ACSR	Str.	Sol.			
PIK88		10	8	.116-.128	Brown		10	8	.116-.128	Brown	5/8 or BG
PIK68		8	6	.145-.162	Green		10	8	.116-.128	Brown	
PIK66		8	6	.145-.162	Green		8	6	.145-.162	Green	
PIK48	6-6/1	5-6	4	.184-.206	Blue		10	8	.116-.128	Brown	
PIK46	6-6/1	5-6	4	.184-.206	Blue		8	6	.145-.162	Green	
PIK44	6-6/1	5-6	4	.184-.206	Blue	6-6/1	5-6	4	.184-.206	Blue	
PIK28	4-6/1, 7/1	3-4	2	.232-.260	Orange		10	8	.116-.128	Brown	
PIK26	4-6/1, 7/1	3-4	2	.232-.260	Orange		8	6	.145-.162	Green	
PIK24	4-6/1, 7/1	3-4	2	.232-.260	Orange	6-6/1	5-6	4	.184-.206	Blue	
PIK22	4-6/1, 7/1	3-4	2	.232-.260	Orange	4-6/1, 7/1	3-4	2	.232-.260	Orange	
PIK18	2-6/1, 7/1	1-2		.292-.332	Red		10	8	.116-.128	Brown	
PIK16	2-6/1, 7/1	1-2		.292-.332	Red		8	6	.145-.162	Green	
PIK14	2-6/1, 7/1	1-2		.292-.332	Red	6-6/1	5-6	4	.184-.206	Blue	
PIK12	2-6/1, 7/1	1-2		.292-.332	Red	4-6/1, 7/1	3-4	2	.232-.260	Orange	
PIK11	2-6/1, 7/1	1-2		.292-.332	Red	2-6/1, 7/1	1-2		.292-.332	Red	
PIK08		1/0		.373	Yellow		10	8	.116-.128	Brown	
PIK06		1/0		.373	Yellow		8	6	.145-.162	Green	
PIK04		1/0		.373	Yellow	6-6/1	5-6	4	.184-.206	Blue	
PIK02		1/0		.373	Yellow	4-6/1, 7/1	3-4	2	.232-.260	Orange	
PIK01		1/0		.373	Yellow	2-6/1, 7/1	1-2		.292-.332	Red	
PIK00		1/0		.373	Yellow		1/0		.373	Yellow	