

Project: \_\_\_\_\_ Type: \_\_\_\_\_

Drawn by: \_\_\_\_\_ Catalogue #: \_\_\_\_\_ Date: \_\_\_\_\_

## Individual Spec Sheet

# LED HIGH INTENSITY LAMP

CCT and Power Selectable

### ORDERING INFORMATION

**Order code:** 69128  
**Model number:** CRN/PS120W/2CCT/BYP/120-277/EX39/STD  
**UPC:** 069549024779  
**Case quantity:** 6  
**DLC Unique ID:** S-JFKDSB

### PHYSICAL DATA

**Base:** EX39  
**Type:** 360° High Intensity

### PERFORMANCE DATA

**Watts (W):** 84/120  
**Traditional equivalent (W)** 400  
**Volts (V AC):** 120-277  
**Color temperature (K)<sup>1</sup>:** 4 000/5 000  
**Lumen output (lm)<sup>2</sup>:** 10 248/14 404  
**Efficacy (lm/W):** 122/122.17  
**CRI:** 80  
**Life L70 (h)<sup>3</sup>:** 50 000  
**Beam angle (°):** 360  
**Power factor:** >0.9  
**Frequency (Hz):** 50/60  
**Operating temp. range:** - 40 °C / - 40 °F to 45 °C / 113 °F  
**Installation:** Ballast Bypass

<sup>1</sup> Typical color temperature range: +/- 5 %.


<sup>2</sup> Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.

<sup>3</sup> Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations.

### LUMEN SPECIFICATION TABLE

Order code	Description	Watts (W)	4 000/5 000 K	
			Lumen output (lm)	Efficacy (lm/W)
69128	CRN/PS120W/2CCT/BYP/120-277/EX39/STD	84	10 248 lm	122 lm/W
		120	14 404 lm	122.17 lm/W

### DIMENSIONS



This lighting equipment meets requirements of ICES-005 issue 5 class B for use in residential applications. Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.



ICES  
005



enclosed  
fixture

