



Catalog N°:
KSU20

BURNDY Catalog Number	KSU20
UPC Number	781810035252
Description	SERVIT UNIV 4R-4T CU TN
Status	Active
Web Use	
BURNDY Product Line	
Dimensional	
Width (in)	.48
Cross Flats	.69
General	
Product Description	Tin-plated, high strength copper alloy SERVIT® with spacer. Spacer separates dissimilar conductors and provides long contact length that prevents high pressure point contacts between run and tap conductors.





Conductor(s)	
Copper Tap Range	10 AWG-4 AWG
CopperWeld Solid Run Size (Range)	N/A
Copper Stranded Run (Range)	8 AWG-2 AWG
CopperWeld Stranded Tap Size (Range)	N/A
Copper Solid Tap (Range)	10 AWG-4 AWG
CopperWeld Solid Tap Size (Range)	N/A
Copper Solid Run Size (Range)	10 AWG-4 AWG
CopperWeld Stranded Run Size (Range)	N/A
Physical	
Installation Torque	165
Type of Plating	Tin - Electro Plated
Connector Type	Split Bolt
Plated (Yes or No)	Y
Product Material	Copper
Approvals / Certifications	
UL Listed	Y





CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

