



# LED replacement lamps


## LED HID Type A

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (ln)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	#Location Rating	Additional Information	
<b>400 Watt Metal Halide Replacement Lamp</b>																	
	EX39	60	43263	LED60/2M175/740		3	8.4	8,800		4000	70	175W	50,000	-	Damp	Open or Closed Rated, CWA ANSI -M57, M137, M152	
			88107	LED60/2M175/750		3	8.4	8,800		5000	70	175W	50,000	-	Damp	Open or Closed Rated, CWA ANSI -M57, M137, M152	
	80	43258	LED80/2M250/740			3	8.4	11,800		4000	70	250W	50,000	-	Damp	Open or Closed Rated, CWA ANSI -M58, M138, M153	
			88099	LED80/2M250/750			3	8.4	11,800		5000	70	250W	50,000	-	Damp	Open or Closed Rated, CWA ANSI -M58, M138, M153
	130	43252	LED130/2M400/740			3	8.4	18,500		4000	70	400W	50,000	-	Damp	Open or Closed Rated, CWA, ANSI -M59, M135, M155	
			88109	LED130/2M400/750			3	8.4	18,500		5000	70	400W	50,000	-	Damp	Open or Closed Rated, CWA, ANSI -M59, M135, M155
	165	21259	LED165/M400/740			3	11.42	20,000		4000	73	400	50,000	-	Dry	Open Rated Only, CWA, ANSI -M59, M135, M155	

## LED HID Type B

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (ln)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	#Location Rating	Additional Information	
<b>LED Replacement Lamps for HID</b>																	
	MED	50	22779	LED50ED23.5M/740	120-277	3	7.7	7,500		4000	>70	100W	50,000	-	Damp	Coming Soon	
		80	22768	LED80ED23.5M/740	120-277	3	7.7	12,000		4000	>70	175W	50,000	-	Damp	Coming Soon	
	EX39	50	22679	LED50ED23.5/740	120-277	3	7.7	7,500		4000	>70	100W	50,000	-	Damp	Coming Soon	
			22739	LED50ED23.5/750	120-277	3	7.7	7,500		5000	>70	100W	50,000	-	Damp	Coming Soon	
	80	22635	LED80ED23.5/740	120-277	3	7.7	12,000		4000	>70	175W	50,000	50,000	-	Damp	Coming Soon	
			22676	LED80ED23.5/750	120-277	3	7.7	12,000		5000	>70	175W	50,000	50,000	-	Damp	Coming Soon
	115	22622	LED115ED28/740	120-277	3	8.3	18,000		4000	>70	250W	50,000	50,000	-	Damp	Open and Closed Rated -Ballast bypass required.	
			22623	LED115ED28/750	120-277	3	8.3	18,000		5000	>70	250W	50,000	50,000	-	Damp	Open and Closed Rated -Ballast bypass required.
	150	22611	LED150ED28/740	120-277	3	8.3	23,500		4000	>70	400W	50,000	50,000	-	Damp	Open and Closed Rated -Ballast bypass required.	
			22613	LED150ED28/750	120-277	3	8.3	23,500		5000	>70	400W	50,000	50,000	-	Damp	Open and Closed Rated -Ballast bypass required.

## 4 Pin Plug-In

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (ln)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	#Location Rating	Additional Information
<b>Vertical</b>																
	Plug-In	G24q/GX24	12	96801	LED12G24Q-V/827	#	6	5.31	950		2700	80	50000	-	Damp	Requires Electronic Ballast, White
				96775	LED12G24Q-V/830	#	6	5.31	950		3000	80	50000	-	Damp	Requires Electronic Ballast, White
				96689	LED12G24Q-V/835	#	6	5.31	1000		3500	80	50000	-	Damp	Requires Electronic Ballast, White
				96771	LED12G24Q-V/840	#	6	5.31	1000		4000	80	50000	-	Damp	Requires Electronic Ballast, White
		GX24q	18.5	39288	LED19GX24q-V/827	#	6	6.42	1800		2700	80	50000	-	Damp	Requires Electronic Ballast, White
				39277	LED19GX24q-V/830	#	6	6.42	1850		3000	80	50000	-	Damp	Requires Electronic Ballast, White
				39275	LED19GX24q-V/835	#	6	6.42	1950		3500	80	50000	-	Damp	Requires Electronic Ballast, White
				39279	LED19GX24q-V/840	#	6	6.42	1950		4000	80	50000	-	Damp	Requires Electronic Ballast, White
<b>Horizontal</b>																
	Plug-In	G24q/GX24	12	96799	LED12G24Q-H/827	#	6	5.31	950		2700	80	50000	-	Damp	Requires Electronic Ballast, White
				96798	LED12G24Q-H/830	#	6	5.31	950		3000	80	50000	-	Damp	Requires Electronic Ballast, White
				96761	LED12G24Q-H/835	#	6	5.31	1000		3500	80	50000	-	Damp	Requires Electronic Ballast, White
				96769	LED12G24Q-H/840	#	6	5.31	1000		4000	80	50000	-	Damp	Requires Electronic Ballast, White
		GX24q	18.5	39289	LED19GX24q-H/827	#	6	6.7	1800		2700	80	50000	-	Damp	Requires Electronic Ballast, White
				39282	LED19GX24q-H/830	#	6	6.7	1850		3000	80	50000	-	Damp	Requires Electronic Ballast, White
				39276	LED19GX24q-H/835	#	6	6.7	1950		3500	80	50000	-	Damp	Requires Electronic Ballast, White
				39283	LED19GX24q-H/840	#	6	6.7	1950		4000	80	50000	-	Damp	Requires Electronic Ballast, White

# - Check compatibility at [GELighting.com/LED4pin-compatibility](http://GELighting.com/LED4pin-compatibility)

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com>