

QO120PLILC

Mini circuit breaker, QO, 20A, 1 pole,
120/240VAC, 10kA, Powerlink, load shedding,
plug in mount



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	1P
Ratings	Switching Duty rated
Electrical Connection	Box lugs

Complementary

Interrupt Rating	10 kA 120/240 V AC 50/60 Hz
Number of Panel Spaces	1
Wire Size	AWG 12...AWG 2 aluminium
Tightening Torque	35.40 lbf.in (4 N.m)
Height	4.57 in (116 mm)
Width	0.75 in (19 mm)
Depth	2.91 in (74 mm)
Net Weight	0.47 lb(US) (0.213 kg)

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	00026-QO- PLILC BREAKERS - INTELLIGENT LOAD CENTER
Discount Schedule	DE2A
GTIN	785901446477
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.80 in (9.652 cm)
Package 1 Width	1.30 in (3.302 cm)
Package 1 Length	5.50 in (13.97 cm)
Package 1 Weight	7.36 oz (208.655 g)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------