

Product data sheet

Characteristics

9998L44

Contacteur, Type L, multipole lighting, remplacement coil, 110/120VAC 50/60Hz, 8903L
2 to 6 poles, 8903LX 2 to 4 poles



Main

Product or Component Type	Coil
Accessory / separate part destination	Class 8903 contactor

Complementary

[Ue] rated operational voltage	120 V AC 60 Hz 110 V AC 50 Hz
Inrush power in VA	150 VA 140 VA
Average consumption	30 VA
Height	2.38 in (60.5 mm)
Width	2.11 in (53.6 mm)
Depth	1.46 in (37.1 mm)

Ordering and shipping details

Category	21756-9998 DISCOUNT CP10
Discount Schedule	CP10
GTIN	785901081210
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.09 in (5.3 cm)
Package 1 Width	2.80 in (7.1 cm)
Package 1 Length	3.39 in (8.6 cm)
Package 1 Weight	5.76 oz (163.3 g)

Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------