

LC1D65004G6

IEC contactor, TeSys D, nonreversing, 80A resistive, 4 pole, 4 NO, 120VAC 60Hz coil, open style



Main

Range of Product	TeSys Deca
Product or Component Type	Contacteur
Device short name	LC1D
Contacteur application	Resistive load
Utilisation category	AC-1 AC-3 AC-3e AC-4
Poles description	4P
[Ue] rated operational voltage	Power circuit <= 690 V AC 25...400 Hz
[Ie] rated operational current	80 A (at <140 °F (60 °C)) AC AC-1 for power circuit
[Uc] control circuit voltage	120 V AC 60 Hz

Complementary

Maximum Horse Power Rating	10 Hp at 230/240 V AC 60 Hz for 1 phase motors conforming to CSA 10 Hp at 230/240 V AC 60 Hz for 1 phase motors conforming to UL 20 Hp at 200/208 V AC 60 Hz for 3 phase motors conforming to CSA 20 Hp at 200/208 V AC 60 Hz for 3 phase motors conforming to UL 20 Hp at 230/240 V AC 60 Hz for 3 phase motors conforming to CSA 20 Hp at 230/240 V AC 60 Hz for 3 phase motors conforming to UL 5 Hp at 115 V AC 60 Hz for 1 phase motors conforming to CSA 5 Hp at 115 V AC 60 Hz for 1 phase motors conforming to UL 50 Hp at 460/480 V AC 60 Hz for 3 phase motors conforming to CSA 50 Hp at 460/480 V AC 60 Hz for 3 phase motors conforming to UL 50 Hp at 575/600 V AC 60 Hz for 3 phase motors conforming to CSA 50 hp at 575/600 V AC 60 Hz for 3 phase motors conforming to UL
Compatibility code	LC1D
Pole contact composition	4 NO
Protective cover	With
[Ith] conventional free air thermal current	10 A (at 140 °F (60 °C)) for control circuit 80 A (at 140 °F (60 °C)) for power circuit
Irms rated making capacity	1000 A at 440 V for power circuit conforming to IEC 60947 140 A AC for control circuit conforming to IEC 60947-5-1
Rated breaking capacity	1000 A at 440 V for power circuit conforming to IEC 60947
Associated fuse rating	10 A gG for control circuit conforming to IEC 60947-5-1 125 A gG at <= 690 V coordination type 1 for power circuit 125 A gG at <= 690 V coordination type 2 for power circuit
Average impedance	1 mOhm - Ith 80 A 50 Hz for power circuit
Power dissipation per pole	6.4 W AC-1
[Ui] rated insulation voltage	Control circuit 600 V CSA Control circuit 600 V UL Power circuit 600 V CSA Power circuit 600 V UL Control circuit 690 V IEC 60947-1 Power circuit 690 V IEC 60947-1
Overvoltage category	III
[Uimp] rated impulse withstand voltage	8 kV IEC 60947
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Mechanical durability	6000000 cycles
Control circuit type	AC 60 Hz standard
Coil technology	Without built-in bidirectional peak limiting diode suppressor
Control circuit voltage limits	0.3...0.6 Uc 140 °F (60 °C) drop-out AC 60 Hz 0.85...1.1 Uc 140 °F (60 °C) operational AC 60 Hz
Inrush power in VA	140 VA cos phi 0.75 (at 68 °F (20 °C))
Hold-in power consumption in VA	13 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 15 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat dissipation	4...5 W at 50/60 Hz for control circuit
Operating time	12...26 ms closing 4...19 ms opening
Maximum operating rate	3600 cyc/h 140 °F (60 °C)
Connections - terminals	Control circuit: screw clamp terminal 1 0.00...0.01 in ² (1...4 mm ²) - cable stiffness: solid without cable end Control circuit: screw clamp terminal 2 0.00...0.01 in ² (1...4 mm ²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminal 2 0.00...0.01 in ² (1...4 mm ²) - cable stiffness: solid without cable end Power circuit: screw clamp terminal 1 0.00...0.05 in ² (1...35 mm ²) - cable stiffness: solid without cable end Power circuit: screw clamp terminal 2 0.00...0.04 in ² (1...25 mm ²) - cable stiffness: solid without cable end
Tightening torque	Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminal flat Ø 6 mm Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminal Philips No 2 Power circuit 44.25 lbf.in (5 N.m) screw clamp terminal flat Ø 6 mm Power circuit 44.25 lbf.in (5 N.m) screw clamp terminal flat Ø 8 mm Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminal pozidriv No 2 Power circuit 44.25 lbf.in (5 N.m) screw clamp terminal pozidriv No 2
Auxiliary contacts type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Minimum switching voltage	17 V for control circuit
Minimum switching current	5 mA for control circuit
Insulation resistance	> 10 MOhm for control circuit
Non-overlap time	1.5 Ms on de-energisation between NC and NO contacts 1.5 ms on energisation between NC and NO contacts
Mounting Support	Plate Rail

Environment

Standards	EN 60947-5-1 IEC 60947-4-1 UL 508 EN 60947-4-1 CSA C22.2 No 14 IEC 60947-5-1
Product Certifications	DNV[RETURN]LROS (Lloyds register of shipping) [RETURN]RINA[RETURN]JUL[RETURN]CCC[RETURN]CSA[RETURN]GOST[RETURN]JGL[RETURN]
IP degree of protection	IP2X IEC 60529 IP2X VDE 0106
Protective treatment	TH 3)IEC 60068
Permissible ambient air temperature around the device	23...140 °F (-5...60 °C) -40...158 °F (-40...70 °C) at Uc
Operating altitude	9842.52 ft (3000 m) without derating
Fire resistance	1562 °F (850 °C) IEC 60695-2-1
Flame retardance	V1 conforming to UL 94
Mechanical robustness	Shocks contactor open 8 Gn for 11 ms) Shocks contactor closed 10 Gn for 11 ms) Vibrations contactor opened 2 Gn, 5...300 Hz) Vibrations contactor closed 3 Gn, 5...300 Hz)
Height	5.00 in (127 mm)
Width	3.35 in (85 mm)
Depth	5.12 in (130 mm)
Net Weight	3.17 lb(US) (1.44 kg)

Ordering and shipping details

Category	22357-CTR, TESYS D, OPEN, 40-65A AC
Discount Schedule	I12
GTIN	3389110072426
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.12 in (13.0 cm)
Package 1 Width	3.74 in (9.5 cm)
Package 1 Length	5.31 in (13.5 cm)
Package 1 Weight	3.17 lb(US) (1.44 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------