

Specifications



Photo is representative



Eaton DSD918 S769

Eaton Crouse-Hinds series DSD front operated pushbutton cover and device sub-assembly, 10A, Red, Feraloy iron alloy, 1 circuit universal, 1 button, Maintained red emergency "STOP" button with lockout, factory sealed, 600 Vac

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series DSD front operated pushbutton cover and device sub-assembly
CATALOG NUMBER	DSD918 S769
PRODUCT LENGTH/DEPTH	5.25 in
PRODUCT HEIGHT	3.5 in
PRODUCT WIDTH	5 in
PRODUCT WEIGHT	3.8 lb



Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Division 2 Class II, Division 1 Class II, Division 2 Class III
NEMA RATING	3 7 9

Resources

CATALOGUES	DSD and DSDX Cover and Device Sub-assemblies catalog page
CERTIFICATION REPORTS	DSD Explosionproof Cover and Device Sub-assemblies UL certification DSD Explosionproof Cover and Device Sub-assemblies Canadian certification
INSTALLATION INSTRUCTIONS	IF 1929 - Toggle Operator for EDS, EDSX, EFD, DSD and DSDX Series IF 1424 - DSD, GFS, CPS and ENR Series Replacement Covers IF 899 - EDSX, EDS, EFS, DSDX and DSD Control Stations
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DSD918 S769

Product specifications

VOLTAGE RATING	600 Vac
NUMBER OF COVER BUTTONS	1
NORMAL POSITION	1 circuit universal
AMPERAGE RATING	10A
COLOR	Red
MATERIAL	Feraloy iron alloy
SPECIAL FEATURES	Maintained red emergency "STOP" button with lockout, factory sealed

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Follow us on social media to get the latest product and support information.

All other trademarks are property of their respective owners.

