

# Product data sheet

Specifications

SQUARE D



## LOADCENTRE HOM SECONDARY SURGE ARRESTOR

HOM2175SB

### Main

Product	Surge protection device
Range	Homeline

### Complementary

Voltage Rating	120/240 V AC
MCOV	150 V 300 V
SCCR	25 kA
Surge Current	25 kA
Rated Current	10 kA
Number of Phases	1 phase
Wiring Configuration	3-wire
Local Signalling	1 LED green normal operation
Product destination	Load center Homeline
Height	3.7 in (94.0 mm)
Width	2 in (50.8 mm)
Depth	2.6 in (66.04 mm)

### Environment

Ambient Operating	149 °F (65 °C)
Enclosure Rating	NEMA 1
Standards	UL 1449:ed. 4 type II

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.20 in (5.588 cm)
Package 1 Width	2.70 in (6.858 cm)
Package 1 Length	6.20 in (15.748 cm)
Package 1 Weight	6.080 oz (172.365 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	20

<b>Package 2 Height</b>	7.20 in (18.288 cm)
<b>Package 2 Width</b>	5.80 in (14.732 cm)
<b>Package 2 Length</b>	21.40 in (54.356 cm)
<b>Package 2 Weight</b>	8.179 lb(US) (3.710 kg)

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 251

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No