

Product data sheet

Characteristics

M8650A4C0H6C7C3A

ION8650 meter 128MB, FT21 panel,
120VAC/160VDC 60Hz, Full comm 1I+5O,
RMICAN



Main

Range	PowerLogic
Device short name	ION8650A
Product or Component Type	Revenue and power quality meter

Complementary

Power quality analysis	IEC 61000-4-15 flicker Magnitude harmonic up to the 50th Transient capture EN 50160 ed. 4 compliance report Harmonic distortion Voltage sag and swell detection Waveform capture Programmability (logic and math functions) Up to the 63rd harmonic IEC 61000-4-30 class A power quality measurement
Device Application	Load curtailment Instrument transformer correction Equipment monitoring and control Co-generation and IPP monitoring Tariff metering Demand and power factor control Energy pulsing and totalisation
Type of measurement	Current Voltage Frequency Apparent power total Power factor total Apparent power per phase Power factor per phase Active power total Active power per phase Reactive power total Reactive power per phase
[Us] rated supply voltage	120...277 V AC 47...63 Hz 120...480 V AC 47...63 Hz 65...120 V AC 47...63 Hz 80...160 V DC
Network Frequency	60 Hz
Outlet standard	American
Line Rated Current	5 A 2 A 1 A
Poles description	3P 1P + N 3P + N
Power consumption in VA	24 VA
Maximum power consumption in VA	33 VA
Display Type	FSTN transfective LCD

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Form designation	36S 2½-element 4 9 3-element 4 35 2-element 3 29 2½-element 4
Sampling rate	1024 samples/cycle
Measurement current	0.001...24 A
Analogue input type	Current 0.01...20 A (impedance 0.05 Ohm)
Measurement voltage	57...277 V AC phase to neutral 100...480 V AC phase to phase
Number of inputs	1 digital 0.001...100 mA 30 V DC
Measurement accuracy	Current 0.1 % Voltage 0.1 % Power 0.1 % Power factor 0.1 % Frequency 0.001 Hz Energy 0.1 %
Accuracy class	Class 0.2S energy IEC 62053-23 Class 0.2 energy ANSI C12.20 Class 0.2S energy IEC 62053-22
Number of Outputs	2 pulse 4 form C relay output 1 form A triac output
Communication port protocol	DNP3 300...115200 bauds ION 300...115200 bauds Ansi C12.18 <= 19200 bauds IEC 61850 ed. 2 10/100 Mbit/s TCP/IP 10/100 Mbit/s DLMS 300...115200 bauds Modbus 57600 bauds TCP/IP 300...57600 bauds DNP3 10/100 Mbit/s ION 10/100 Mbit/s Modbus RTU, master/slave 300...115200 bauds Modbus TCP, master/slave 10/100 Mbit/s ModemGate EtherGate
Communication port support	RJ45 ETHERNET SUB-D 9 RS485/RS232 Terminal block RS485 Infrared RJ11 modem
Time synchronisation protocol	IRIG-B GPS: Truetime/Datum
Data recording	Data logs Transient logs Revenue logs Historical logs Harmonics logs Time stamping Event logs Sag and swell logs GPS synchronisation Alarms
Transmission Rate	300...57600 bauds <= 19200 bauds 300...115200 bauds 10/100 Mbit/s 57600 bauds
Memory capacity	128 MB
Web services	Port addressing user designed Alarm notification by e-mail Robust security logs Web server
Ethernet service	Enable/Disable serial ports Enable/Disable Ethernet protocols SNMP-Traps and SYSLOG
Tamperproof of settings	RMICAN protected
Provided Equipment	Break out panel
Compatibility code	ION8650A

Environment

Electromagnetic compatibility	Electrostatic discharge immunity test conforming to IEC 61000-4-2 Conducted RF disturbances conforming to IEC 61000-4-6 Immunity to impulse waves conforming to IEC 61000-4-12 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Susceptibility to electromagnetic fields conforming to IEC 61000-4-3 1.2/50 µs shock waves immunity test conforming to IEC 61000-4-5 Conducted and radiated emissions B conforming to CISPR 22
Mounting Mode	Flush-mounted
Enclosure type	FT21 switchboard
Type of Installation	Indoor installation
Overvoltage category	III
IP degree of protection	Front face IP50 Back IP30
Relative humidity	5...95 %
Pollution degree	2
Ambient air temperature for operation	-40...185 °F (-40...85 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Operating altitude	0...9842.52 ft (0...3000 m)
Standards	ANSI C12.1 IEC 62052-11
Width	6.42 in (163 mm)
Depth	8.98 in (228 mm)
Height	11.22 in (285 mm)
Net Weight	15.43 lb(US) (7 kg)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.42 in (29.0 cm)
Package 1 Width	11.42 in (29.0 cm)
Package 1 Length	16.14 in (41.0 cm)
Package 1 Weight	15.43 lb(US) (7.0 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information