

# TX6A™ Category 6A Shielded Copper Cable – F/UTP

North America

**PANDUIT**<sup>®</sup>  
SPECIFICATION SHEET

## SPECIFICATIONS

Category 6A cable shall be constructed of 23 AWG copper conductors with FEP insulation. The copper conductors shall be twisted in pairs and separated by an integrated pair separator. All four pairs shall be surrounded by an overall metallic foil shield within a flame retardant PVC (CMP) jacket. The TX6A Shielded Copper Cable must be installed as part of a complete TX6A Shielded Copper Cabling System to achieve 10GBASE-T certified performance.



## TX6A Shielded Copper Cable – F/UTP

**CMP:** PFP6X04\*\*-UGZ

\*\*Colors: BU (Blue), WH (White), RD (Red), OR (Orange), YL (Yellow), GR (Green), VL (Violet), IG (International Gray), or BL (Black)

## TECHNICAL INFORMATION

<b>Electrical performance:</b>	Certified channel performance in a 4-connector configuration up to 100m and exceeds the requirement of the ANSI/TIA-568.2-E Category 6A Standards for supporting 10GBASE-T transmission over twisted pair cabling systems as part of the TX6A Shielded Copper Cabling System Certified component performance up to 100m and meets or exceeds the component requirement of the ANSI/TIA-568.2-E Category 6A Standards for supporting 10GBASE-T transmission over twisted-pair cabling systems
<b>Conductors/insulators:</b>	23 AWG solid bare copper wire covered by FEP insulation
<b>Insulation diameter:</b>	0.041 in. - 0.043 in. (1.04mm - 1.09mm)
<b>Flame rating:</b>	NFPA 262
<b>Installation tension:</b>	110 N (25 lbf.) maximum
<b>PoE compliance:</b>	Meets IEEE 802.3af, IEEE 802.3at and IEEE 802.3bt for PoE applications
<b>Temperature rating:</b>	32°F to 140°F (0°C to 60°C) during installation -4°F to 167°F (-20°C to 75°C) during operation
<b>Cable jacket:</b>	Flame retardant PVC (CMP)
<b>Cable diameter:</b>	0.273 in. (6.9mm) nominal
<b>Cable weight:</b>	39 lbs./1000 ft. (18 kg/305m)
<b>Packaging:</b>	1000 ft. (305m) on a reel Packaged tested to ISTA Procedure 1A

## KEY FEATURES AND BENEFITS

<b>Integrated pair divider:</b>	Separates pairs for exceptional cable performance
<b>Overall foil shield:</b>	Provides superior structural integrity and reduces external interference to ensure exceptional cable performance at all swept frequencies up to 500 MHz
<b>Internal drain wire:</b>	Facilitates means of grounding the cable and provides for efficient performance and protection of network investment
<b>Descending length cable markings:</b>	Easy identification of remaining cable reduces installation time and cable scrap
<b>Bulk packaging:</b>	Supplied 1000 ft. (305m) on a reel



All listed part numbers are compliant with the U.S. Trade Agreements Act (TAA) for purchases shipped to customers in the United States.

# TX6A™ Category 6A Shielded Copper Cable – F/UTP

## APPLICATIONS

TX6A Shielded Copper Cable is a component of the TX6A Shielded Copper Cabling System. This end-to-end system provides a cost-effective medium for ensuring that network bandwidth needs are easily met today and tomorrow. The shielded cabling system provides high performance, excellent EMI suppression, and aids in secure data transmission. The solution helps ensure organizations efficiently and reliably meet their data transmission needs. Usage of the TX6A Shielded Copper Cabling System include high bandwidth applications within data centers and connections to high-end workstations such as:

- 10GBASE-T Ethernet
- Data Center applications
- Virtual business management applications

## ADDITIONAL SPECIFICATIONS

Mechanical Test	
Ultimate breaking strength:	> 400 N (90 lbf)
Minimum bend radius:	8 x cable diameter
Engineering Test	
Nominal velocity of propagation (NVP):	71% nominal
Operating voltage, maximum:	80 V

## ENGINEERING DRAWING

