



## Principal

Product	Receptacle Switch
For Use With	Plug ACP6034BC Appleton Powertite
Current Rating	60 A
Enclosure Rating	NEMA 3R/12 Acier galvanisé
Horsepower Rating	15 hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 240.6 30 hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 15 hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 240.6 50 hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 10 hp à 250 V DC conformément à NEC 240.6
Disconnect Type	Fusible disconnect switch
Mounting Type	Saillie
Number of Poles	3
Phase	3 phases
Electrical Connection	Receptacle
Certifications	Listé UL
Voltage Rating	600 V AC 250 V DC
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 cuivre
Wire Configuration	4 fils Sans neutre

## Complémentaire

Largeur	266,70 mm
Hauteur	419,10 mm
Profondeur	177,80 mm

## Emballage

Poids de l'emballage (Kg)	7,711 kg
---------------------------	----------

## Offre de la durabilité

Statut environnemental de l'offre	Produit Green Premium
Régulation REACH	<a href="#">Déclaration REACH</a>
Sans SVHC REACH	Oui
Directive RoHS UE	Conforme <a href="#">Déclaration RoHS UE</a>
Sans mercure	Oui
Information sur les exemptions RoHS	<a href="#">Oui</a>
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Profil environnemental	<a href="#">Profil environnemental du Produit</a>
Sans PVC	Oui