



## Principal

|                        |                                 |
|------------------------|---------------------------------|
| Product Type           | Disjoncteur                     |
| Range                  | PowerPact M                     |
| Breaking Capacity Code | J                               |
| Trip Unit Technology   | Électronique, basic, ET 1.0, LI |

## Complémentaire

|                             |  |
|-----------------------------|--|
| Current Sensor Rating Range | 450 A  |
| Rated Current               | 450 A  |
| Rated Operational Voltage   | 600 V AC   |
| Mounting Mode               | I-Line   |
| Poles Description           | 3P   |
| Breaking Capacity           | 100 kA à 240 V AC<br>65 kA à 480 V AC<br>25 kA à 600 V AC  |
| Circuit Breaker Type        | M-frame  |
| Continuous Current Rating   | 80 %   |
| Electrical Connection       | I-Line connection ligne<br>Cosses charge                   |
| Magnetic Tripping Current   | 900...4500 A   |
| Terminal Identifier         | AL800M23K  |
| AWG Gauge                   | AWG 3/0...500 kcmil (aluminium / cuivre) pour 3 câble(s)   |
| Tightening Torque           | 50 N.m pour 95...240 mm <sup>2</sup> (AWG 3/0...500 kcmil) |
| Height                      | 326,6 mm   |
| Width                       | 8,06 mm  |
| Depth                       | 210 mm   |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environnement

|                |                        |
|----------------|------------------------|
| Certifications | CSA<br>CEI<br>Listé UL |
|----------------|------------------------|

## Emballage

|                           |           |
|---------------------------|-----------|
| Poids de l'emballage (Kg) | 13,154 kg |
|---------------------------|-----------|

## Offre de la durabilité

|                                     |  |
|-------------------------------------|--|
| Statut environnemental de l'offre   | Produit Green Premium  |
| Régulation REACH                    | <a href="#">Déclaration REACH</a>  |
| Directive RoHS UE                   | Conforme<br><a href="#">Déclaration RoHS UE</a>  |
| Sans mercure                        | Oui  |
| Information sur les exemptions RoHS | <a href="#">Oui</a>  |
| Régulation RoHS Chine               | <a href="#">Déclaration RoHS pour la Chine</a><br>Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information. |
| Profil environnemental              | <a href="#">Profil environnemental du Produit</a>  |
| Profil de circularité               | <a href="#">Informations de fin de vie</a>   |
| Sans PVC                            | Oui  |

## Garantie contractuelle

|          |           |
|----------|-----------|
| Garantie | 18 months |
|----------|-----------|