

# HL3IMA16C

Surge protection device, Surgelogic, HL, 160kA, 240/120 VAC delta, 3 phase, 4 wire, SPD type 2



## Principal

Product	Surge protection device
Range	Surgelogic
Device Short Name	IMA
Type	HL

## Complémentaire

Surge Current	160 kA
Voltage Rating	240/120 V delta AC
Number of Phases	3 phases
Wiring Configuration	4 fils
Connection	I-Line line Cosses terre AWG 6 cuivre 4 N.m Cosses neutre AWG 6 cuivre 4 N.m
MCOV	150 V
Max Number of Poles	3
Rated Current	60 A
Breaking Capacity	50 kA
Trip Unit Technology	Thermique-magnétique
SCCR	200 kA
Local Signalling	DEL d'état vert par phase pour opération normale DEL d'état rouge par phase pour erreur
Provided Equipment	Alarm enable/disable switch Surge counter Disjoncteur
Mounting Support	Montage sur panneau
Height	308,9 mm
Width	341,9 mm
Depth	142,1 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

---

Longueur de câble	483 mm
-------------------	--------

---

## Environnement

---

Enclosure Rating	NEMA 2
Standards	UL 1449:ed. 3 UL 1283:ed. 5 CSA C22.2 No 8:1986 UL 96A:ed. 12 UL 489:ed. 11 CSA C22.2 No 5-09

---

## Emballage

---

Poids de l'emballage (Kg)	10,043 kg
---------------------------	-----------

---

## Offre de la durabilité

---

Directive RoHS UE	Conforme <a href="#">Déclaration RoHS UE</a>
Sans mercure	Oui
Information sur les exemptions RoHS	<a href="#">Oui</a>
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

---