


# 8502SFO2V08

NEMA Contactor, Type S, nonreversing, Size 4, 135A, 100 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 208 VAC coil, open



## Principal

Product Type	Contacteur
Type	8502S
Control Circuit Type	Common control circuit
Control Circuit Voltage	208 V AC 60 Hz
Contacteur Type	Non inverseur
Current Rating	135 A
Number of Poles	3P
Phase	3 phases
Horsepower Rating	40 HPà 200 V AC 50 HPà 230 V AC 100 HPà 460 V AC 100 HPà 575 V AC
Maximum Voltage Rating	600 V AC
SCCR	Disjoncteur 225 A maximum, SCCR: 100 kA at 480 V AC Fusible J 200 A maximum, SCCR: 100 kA at 600 V AC Fusible T 200 A maximum, SCCR: 100 kA at 600 V AC Fusible RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fusible RK5 200 A maximum, SCCR: 100 kA at 600 V AC
Control Units	No control units
Pilot Light	Sans signalisation
Auxiliary Contacts	Sans
Control Circuit Fusing	Fusible non fourni
Electrical Connection	Borniers à vis-étrier
Enclosure Type	Not rated (open device)
Certifications	UL listed file E78351 CCN NLDX CSA
NEMA Size	4
Height	208,03 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Depth	165,10 mm
Width	152,40 mm

## Emballage

Poids de l'emballage (Kg)	8,165 kg
---------------------------	----------

## Offre de la durabilité

Régulation REACH	<a href="#">Déclaration REACH</a>
Sans SVHC REACH	Oui
Directive RoHS UE	Non conforme
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

## Garantie contractuelle

Garantie	18 months
----------	-----------