


8502SEO2V07

NEMA Contactor, Type S, nonreversing, Size 3, 90A, 50 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 600 VAC coil, open



Principal

Product Type	Contacteur
Product Range	8502S
Contacteur Type	Non inverseur

Complémentaire

NEMA Size	3
Rated Current	90 A
Number of Poles	3P
Maximum Voltage Rating	600 V AC
Phase	3 phases
Horsepower Rating	25 HPà 200 V AC 30 HPà 230 V AC 50 HPà 460 V AC 50 HPà 575 V AC
SCCR	Disjoncteur 150 A maximum, SCCR: 100 kA at 480 V AC Fusible J 200 A maximum, SCCR: 100 kA at 600 V AC Fusible T 200 A maximum, SCCR: 100 kA at 600 V AC Fusible RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fusible RK5 200 A maximum, SCCR: 100 kA at 600 V AC
Coil Voltage	600 V AC 60 Hz 550 V AC 50 Hz
Control Circuit Type	Common control circuit
Control Units	No control units
Pilot Light	Sans signalisation
Auxiliary Contacts	Sans
Other Equipment	Fusible non fourni
Terminal Type	Borniers à vis-étrier

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Height	180,09 mm
Width	138,94 mm
Depth	165,10 mm

Environnemental

Enclosure Type	Not rated (open device)
Certifications	UL listed file E78351 CCN NLDX CSA

Emballage

Poids de l'emballage (Kg)	6,350 kg
---------------------------	----------

Offre de la durabilité

Régulation REACH	Déclaration REACH
Directive RoHS UE	Non conforme
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

Garantie contractuelle

Garantie	18 months
----------	-----------