

**HDC IP68 16B AS****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The new RockStar® enclosures are resistant to seawater and offer a high degree of shock resistance, meet IP 68 and IP 69K, and have been developed for use under extreme environmental conditions and designed for the high vibration requirements acc. to DIN EN 61373 cat. 2 (bogie). As such, this housing family is ideally suited for fault- and maintenance-free operation of heavy-duty connectors in transport and traffic engineering as well as in power engineering and in applications with extreme requirements. During development, measures were also implemented to make the enclosures extremely EMC-resistant.

**General ordering data**

|            |  |
|------------|--|
| Version    | HDC enclosures, Size: 6, Protection degree: IP66 (in plugged condition), IP68 (in plugged condition), Bulkhead housing, Clamping yoke connection, Standard |
| Order No.  | <a href="#">1081530000</a>   |
| Type       | HDC IP68 16B AS  |
| GTIN (EAN) | 4032248843992  |
| Qty.       | 1 pièce(s)   |

## HDC IP68 16B AS

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Caractéristiques techniques

### Dimensions and weights

|                             |         |                            |            |
|-----------------------------|---------|----------------------------|------------|
| Depth                       | 164 mm  | Depth (inches)             | 6,457 inch |
| Height                      | 29,5 mm | Height (inches)            | 1,161 inch |
| Width                       | 58 mm   | Width (inches)             | 2,283 inch |
| Mounting dimension - height | 32 mm   | Mounting dimension - width | 103 mm     |
| Net weight                  | 180 g   |                            |            |

### Temperatures

|                   |                   |
|-------------------|-------------------|
| Limit temperature | -50 °C ... 125 °C |
|-------------------|-------------------|

### Dimensions

|                      |        |                      |        |
|----------------------|--------|----------------------|--------|
| Height of housing B  | 21 mm  | Hole pitch length A2 | 103 mm |
| Total length housing | 164 mm |                      |        |

### General data

|                   |  |                       |                   |
|-------------------|--|-----------------------|-------------------|
| EMC housings      | Yes  | Housing main material | diecast aluminium |
| Protection degree | IP66 (in plugged condition), IP68 (in plugged condition) | Surface finish        | Powder coating    |

### Version

|                        |                         |                          |                          |
|------------------------|-------------------------|--------------------------|--------------------------|
| BG                     | 6                       | Clamp version            | Clamping yoke connection |
| Colour (RAL)           | RAL 9011, RAL 9005      | Design                   | Standard                 |
| Design of housing      | Bulkhead housing        | Design of locking system | Clamping yoke connection |
| Sealing                | Silicone                | Size                     | 6                        |
| Suitable for ModuPlug® | Yes                     | Top part/bottom part/lid | lower part               |
| Type                   | Bulkhead (feed-through) |                          |                          |

### Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000437    | ETIM 7.0    | EC000437    |
| ETIM 8.0    | EC000437    | ETIM 9.0    | EC000437    |
| ECLASS 9.0  | 27-44-02-02 | ECLASS 9.1  | 27-44-02-02 |
| ECLASS 10.0 | 27-44-02-02 | ECLASS 11.0 | 27-44-02-02 |
| ECLASS 12.0 | 27-44-02-02 | ECLASS 13.0 | 27-44-02-02 |
| ECLASS 14.0 | 27-44-02-02 |             |             |

|                     |                         |
|---------------------|-------------------------|
| Substance           | Acetone                 |
| Chemical resistance | Resistant               |
| Substance           | Diesel oil              |
| Chemical resistance | Unstable                |
| Substance           | Ethyl alcohol           |
| Chemical resistance | Resistant               |
| Substance           | Transmission oil        |
| Chemical resistance | Conditionally resistant |
| Substance           | Hydraulic oil           |
| Chemical resistance | Conditionally resistant |

Date de création 26 novembre 2024 14:10:00 CET

Niveau du catalogue 26.11.2024 / Toutes modifications techniques réservées

**HDC IP68 16B AS**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

**Caractéristiques techniques**

|                     |                         |
|---------------------|-------------------------|
| Substance           | Petroleum benzine       |
| Chemical resistance | Unstable                |
| Substance           | Sweat                   |
| Chemical resistance | Conditionally resistant |
| Substance           | Premium gasoline        |
| Chemical resistance | Unstable                |
| Substance           | Water                   |
| Chemical resistance | Resistant               |
| Substance           | UV                      |
| Chemical resistance | Resistant               |
| Substance           | Ozone                   |
| Chemical resistance | Resistant               |

**Environmental Product Compliance**

|                        |  |
|------------------------|--|
| RoHS Compliance Status | Compliant without exemption  |
| REACH SVHC             | No SVHC above 0.1 wt%  |
| Chemical resistance    | de.myview.objectmodel.impl.BlockImpl@2f2d8f6e de.myview.objectmodel.impl.BlockImpl@2f482f07<br>de.myview.objectmodel.impl.BlockImpl@6a499c6c de.myview.objectmodel.impl.BlockImpl@79ffe372<br>de.myview.objectmodel.impl.BlockImpl@3a6a45dc de.myview.objectmodel.impl.BlockImpl@54347581<br>de.myview.objectmodel.impl.BlockImpl@72383997 de.myview.objectmodel.impl.BlockImpl@745aa0d1<br>de.myview.objectmodel.impl.BlockImpl@1cf65f23 de.myview.objectmodel.impl.BlockImpl@6b19b941<br>de.myview.objectmodel.impl.BlockImpl@585ec134 |

**Important note**

|                     |   |
|---------------------|---|
| Product information | When mounting the housings, make sure that the flat gasket is correctly seated. |
|---------------------|---|

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|   |  |
|---|--|
| Approval/Certificate/Document of Conformity | <a href="#">Manufacturer's declaration</a>   |
| Engineering Data                            | <a href="#">CAD data – STEP</a>  |
| Product Change Notification                 | <a href="#">20220214 Technical change to HDC housings</a><br><a href="#">20220214 Technische Änderung bei HDC-Gehäusen</a> |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>   |
| Brochures                                   | <a href="#">FL FIELDWIRING EN</a><br><a href="#">FL FIELDWIRING EN</a>   |

**Fiche de données**

**HDC IP68 16B AS**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Dessins**

