



Main

Range	ClimaSys
Product name	ClimaSys CV
Product or component type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter 21134.14 Gal/hr(US) (80 m3/h) 50 Hz
[Us] rated supply voltage	10...27.6 V
Input voltage	24 V DC

Complementary

Absorbed power	7.6 W 50 Hz
[In] rated current	0.3 A 50 Hz
Noise level < at	46...49 dB
Bearing type	Ball
Height	170 mm external:
Width	150 mm external:
Depth	62 mm external:
Cut-out dimensions	125 x 125 mm
Net weight	1.06 lb(US) (0.48 kg)
Material	Outlet grille: injected thermoplastic (ASA PC)
Colour	Outlet grille grey RAL 7035)
Ambient air temperature for operation	14...158 °F (-10...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Maximum pressure	50 Pa flow rate 0 m³/h
Connections - terminals	Faston connector
IP degree of protection	IP54
Device composition	1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front 1 cut-out template 1 power cord
Condition of use	Overfrequent filter replacement should be avoided

Outside temperature must be 5 °C lower than inside temperature
Surrounding environment must be relatively clean
Filter must be cleaned and replaced regularly
Flow rates depends on the work point, see ProClima software

Packing Units

Package 1 Weight	1.19 lb(US) (0.540 kg)
Package 1 Height	3.54 in (90.000 mm)
Package 1 width	6.10 in (155.000 mm)
Package 1 Length	7.09 in (180.000 mm)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information

Contractual warranty

Warranty	18 months
----------	-----------