

HDC-CM-4SZF AG**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The CM4 module features the established tension clamp connection. The contact point can be opened with a screwdriver. The wire is then inserted and the contact chamber is then closed when the screwdriver is taken out. A secure connection can be quickly established without the need for any special tools.

A removal tool is available for removing the modules.

General ordering data

Version	Heavy-duty connectors, HDC insert, ConCept module
Order No.	1730120000
Type	HDC-CM-4SZF AG
GTIN (EAN)	4008190384678
Qty.	10 pièce(s)

HDC-CM-4SZF AG

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Caractéristiques techniques

Dimensions and weights

Height	25,4 mm	Height (inches)	1 inch
Width	11,4 mm	Width (inches)	0,449 inch
Length	34 mm	Length (inches)	1,339 inch
Net weight	15 g		

ConCept Pneumatic module

Colour	beige	UL 94 flammability rating	V-0
--------	-------	---------------------------	-----

Dimensions

Height of plug	25,4 mm	Total length base	34 mm
Width	11,4 mm		

General data

Colour	beige	Free from halogens	false
Insulation strength	10 ¹² Ω	Low smoke acc. DIN EN 45545-2	Yes
Material	Polycarbonate, glass fibre reinforced	Number of poles	4
Plugging cycles	≥ 500	Pollution severity	3
Rated current (DIN EN 61984)	14 A	Rated impulse voltage (DIN EN 61984)	6 kV
Rated voltage (DIN EN 61984)	400 V	Series	ConCept module
Surge voltage category	III	Type	Pin
Type of connection	Tension-clamp connection	UL 94 flammability rating	V-0
Volume resistance	1.5 mΩ		

Connection data PE

Connection type PE	Screw connection via module frame
--------------------	-----------------------------------

Version

Conductor cross-section, max.	2,5 mm ²	Conductor cross-section, min.	0,5 mm ²
Material	Polycarbonate, glass fibre reinforced	Stripping length, rated connection	10 mm
Type of connection	Tension-clamp connection	Volume resistance	1.5 mΩ
Wire connection cross section AWG, max.	AWG 14	Wire connection cross section AWG, min.	AWG 20

Classifications

ETIM 6.0	EC002312	ETIM 7.0	EC002312
ETIM 8.0	EC000438	ETIM 9.0	EC000438
ECLASS 9.0	27-44-02-92	ECLASS 9.1	27-44-02-18
ECLASS 10.0	27-44-02-92	ECLASS 11.0	27-44-02-92
ECLASS 12.0	27-44-02-92	ECLASS 13.0	27-44-02-92
ECLASS 14.0	27-44-02-92		

Fiche de données

HDC-CM-4SZF AG

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Caractéristiques techniques

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6c
REACH SVHC	Lead 7439-92-1 Potassium perfluorobutane sulfonate 29420-49-3
SCIP	b67daa31-7dca-434d-8290-da7fb52f83a2

Approvals

Approvals



ROHS	Conform
UL File Number Search	UL Website
Certificate No. (UR)	E92202

Downloads

Approval/Certificate/Document of Conformity	Manufacturer's declaration
Engineering Data	CAD data – STEP
Catalogues	Catalogues in PDF-format
Brochures	FL FIELDWIRING EN

Fiche de données

HDC-CM-4SZF AG

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Dessins

