



### Principal

Product	Combination Starter
Type	S
Control Circuit Type	Separate control circuit

### Complémentaire

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Starter Type	Non réversible
Number of Poles	3P
Horsepower Rating	25 hp à 460 V AC, 3 phases 25 hp à 575 V AC, 3 phases
Maximum Voltage Rating	600 V AC
Control Units	No control units
Pilot Light	Sans signalisation
Auxiliary Contacts	Sans
Type de surcharge thermique	Melting alloy 3
Disconnect Type	Fusible disconnect switch, type H fusible, 60 A
Taille NEMA	2

### Environnement

Enclosure Type	NEMA 4/4X acier inoxydable et with external reset
----------------	---

### Emballage

Poids de l'emballage (Kg)	27,216 kg
---------------------------	-----------

### Offre de la durabilité

Régulation REACh	<a href="#">Déclaration REACh</a>
------------------	-----------------------------------

Directive RoHS UE	Non conforme
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

### Garantie contractuelle

Garantie	18 months
----------	-----------