


# 8736SCO7V02S

NEMA Starter, Type S, reversing, vertical, Size 1, 27A, 10 HP at 575 VAC, 5 kA SSCR, 3 phase, 3 pole, melting alloy overload, 120 VAC coil, open



## Principal

Product Type	Starter
Product Range	S
Starter Type	Réversible

## Complémentaire

NEMA Size	1
Rated Current	27 A
Number of Poles	3P
Mounting Orientation	Vertical
Wiring Mode	3 fils
Maximum Voltage Rating	600 V AC
Phase	3 phases
Type of Overload	Melting alloy 3
Horsepower Rating	7.5 HP at 200 V AC 7.5 HP at 230 V AC 10 HP at 460 V AC 10 HP at 575 V AC
SCCR	Disjoncteur: 5 kA at 600 V AC Fusible: 5 kA at 600 V AC
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control Circuit Type	Separate control circuit
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Terminal Type	Borniers à vis-étrier

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Height	292,61 mm
Width	138,94 mm
Depth	134,87 mm

## Environnement

Enclosure Type	Not rated (open device)
Certifications	Listé UL CSA

## Emballage

Poids de l'emballage (Kg)	4,754 kg
Hauteur de l'emballage 1	21,844 cm
Largeur de l'emballage 1	28,702 cm
Longueur de l'emballage 1	35,052 cm

## Offre de la durabilité

Directive RoHS UE	Non conforme
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

## Garantie contractuelle

Garantie	18 months
----------	-----------