

8536SDA1V06

NEMA Motor Starter, Type S, nonreversing, Size 2, 45A, 25 HP at 460 VAC, 5 kA SCCR, 3 phase, 3 pole, melting alloy, 480 VAC coil, NEMA 12



Principal

| | |
|---------------|--------------------|
| Product Type | Démarrateur moteur |
| Product Range | S |
| Starter Type | Non réversible |

Complémentaire

| | |
|------------------------|--|
| NEMA Size | 2 |
| Rated Current | 45 A |
| Number of Poles | 3P |
| Maximum Voltage Rating | 600 V AC |
| Phase | 3 phases |
| Type of Overload | Melting alloy 3 |
| Horsepower Rating | 10 HP at 200 V AC 15 HP at 230 V AC 25 HP at 460 V AC 25 HP at 575 V AC |
| SCCR | Disjoncteur: 5 kA at 600 V AC Fusible: 5 kA at 600 V AC |
| Coil Voltage | 440 V AC 50 Hz 480 V AC 60 Hz |
| Control Circuit Type | Common control circuit |
| Control Units | No control units |
| Pilot Light | Without pilot light |
| Auxiliary Contacts | Sans |
| Terminal Type | Borniers à vis-étrier |
| Height | 406,40 mm |
| Width | 206,50 mm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------|-----------|
| Depth | 235,71 mm |
|-------|-----------|

Environnement

| | |
|----------------|-------------------------------|
| Enclosure Type | NEMA 12 feuille d'acier peint |
| Certifications | Listé UL CSA NEMA |

Emballage

| | |
|---------------------------|-----------|
| Poids de l'emballage (Kg) | 9,825 kg |
| Hauteur de l'emballage 1 | 26,670 cm |
| Largeur de l'emballage 1 | 27,178 cm |
| Longueur de l'emballage 1 | 42,672 cm |

Offre de la durabilité

| | |
|-------------------------------------|--|
| Régulation REACH | Déclaration REACH |
| Directive RoHS UE | Conforme Déclaration RoHS UE |
| Sans mercure | Oui |
| Information sur les exemptions RoHS | Oui |
| Régulation RoHS Chine | Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information. |
| Sans PVC | Oui |

Garantie contractuelle

| | |
|----------|-----------|
| Garantie | 18 months |
|----------|-----------|