



Principal

| | |
|----------------------|----------------------|
| Marketing Trade Name | QO |
| Product | Load Center |
| Cover Type | Couvercle en saillie |

Complémentaire

| | |
|--|---|
| Tightening Torque | Main lugs: 50 livres par pouce, AWG 8, aluminium / cuivre Main lugs: 50 lb.in, AWG 6...AWG 1/0, aluminium/copper |
| Load Center Type | Fixed Mains (lugs) |
| Rated Current | 100 A |
| Number of Spaces | 6 |
| Max Short Circuit Current Rating | 10 kA |
| Maximum Number of Single Pole Circuits | 12 |
| Maximum Number of Tandem Breakers | 6 |
| Number of Phases | Monophasé |
| Voltage Rating | 120/240 V CA |
| Wire Size | AWG 8...AWG 1 aluminium / cuivre |
| Electrical Connection | Cosses |
| Grounding Bar | Grounding bar (ordered separately) |
| Electrical Connection | Lugs |
| Wiring Configuration | Type 3 fils avec neutre |
| Busbar Material | Tin plated aluminium: busbar |
| Enclosure Material | Feuille d'acier soudé |
| Cover Finish | Baked enamel grey |
| Box Number | 4 |
| Height | 319 mm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------|--------|
| Width | 226 mm |
|-------|--------|

Environnement

| | |
|---------------------------------------|------------------------|
| Enclosure Rating | NEMA 1 pour intérieure |
| Ambient Air Temperature for Operation | -5 °C 40 °C |
| Product Certifications | Listé UL |

Emballage

| | |
|---------------------------|-----------|
| Poids de l'emballage (Kg) | 3,665 kg |
| Hauteur de l'emballage 1 | 11,430 cm |
| Largeur de l'emballage 1 | 27,178 cm |
| Longueur de l'emballage 1 | 36,830 cm |

Offre de la durabilité

| | |
|-------------------------------------|---|
| Statut environnemental de l'offre | Produit Green Premium |
| Régulation REACH | Déclaration REACH |
| Sans SVHC REACH | Oui |
| Directive RoHS UE | Conforme Déclaration RoHS UE |
| Sans métaux lourds toxiques | Oui |
| Sans mercure | Oui |
| Information sur les exemptions RoHS | Oui |
| Régulation RoHS Chine | Déclaration RoHS pour la Chine Déclaration pro-active RoHS pour la Chine (en dehors du périmètre légal RoHS pour la Chine) |
| Profil environnemental | Profil environnemental du Produit |

Garantie contractuelle

| | |
|----------|-----------|
| Garantie | 18 months |
|----------|-----------|