



Principal

| | |
|-------------------|-------------------------|
| Product | Surge protection device |
| Range | Surgelogic |
| Device Short Name | IMA |

Complémentaire

| | |
|---------------------------|--|
| Surge Current | 240 kA par phase |
| Voltage Rating | 208Y/120 V AC |
| Number of Phases | 3 phases |
| Wiring Configuration | 4 fils |
| Connection | Cosses AWG 12...AWG 2 aluminium / cuivre 4 N.m |
| MCOV | 150 V |
| Nominal Discharge Current | 20 kA |
| SCCR | 200 kA |
| Provided Equipment | Alarm enable/disable switch Diagnostic display Backplane Câbles |
| Height | 155,7 mm |
| Width | 250,4 mm |
| Depth | 92,7 mm |

Environnement

| | |
|------------------|---|
| Enclosure Rating | NEMA 2 |
| Standards | UL 1449:ed. 4 CSA C22.2 No 8:1986 UL 96A:ed. 12 UL 1283 IEC 61643-1 |

Emballage

| | |
|---------------------------|----------|
| Poids de l'emballage (Kg) | 3,901 kg |
|---------------------------|----------|

Offre de la durabilité

| | |
|-------------------------------------|--|
| Régulation REACH | Déclaration REACH |
| Directive RoHS UE | Conforme Déclaration RoHS UE |
| Sans mercure | Oui |
| Information sur les exemptions RoHS | Oui |
| Régulation RoHS Chine | Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information. |