

THM WO 12/18 WS**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Similar to illustration

THM WriteOn cable markers on reels are used for labeling conductors and cables with an outside diameter of up to 36 mm. The transparent adhesive strip fixes and protects the printing on the marker surface.

- Protection of the marking against dirt and abrasion by wrapping it with the transparent adhesive strip
- Simple and quick printing with the high-quality thermal transfer printers

General ordering data

| | |
|--------------------|-------------------------------------------------------------------|
| Version | THM, Conductor and cable markers, 1.9 - 1.9 mm, 12 x 18 mm, white |
| Order No. | 1856640000 |
| Type | THM WO 12/18 WS |
| GTIN (EAN) | 4032248399581 |
| Qty. | 1 pièce(s) |
| compatible printer | 2599430000 2599440000 |

THM WO 12/18 WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Caractéristiques techniques

Dimensions and weights

| | | | |
|------------|----------|-----------------|------------|
| Depth | 0,025 mm | Depth (inches) | 0,001 inch |
| Height | 12 mm | Height (inches) | 0,472 inch |
| Width | 18 mm | Width (inches) | 0,709 inch |
| Net weight | 492 g | | |

Temperatures

| | |
|-----------------------------|--------------|
| Operating temperature range | -40...150 °C |
|-----------------------------|--------------|

General data

| | | |
|----------------------------------------------|--------------------------------------------|------------|
| Adhesive | Polyacrylate adhesive | |
| Approval acc. to UL 969 | Yes | |
| Colour | white | |
| Halogen | No | |
| Material | Polyester film | |
| Material colour according to resistance code | 9 | |
| Number of markers per combination | 1 Label reel = Conductor and cable markers | |
| Number of markers per packaging unit | Form of supply | Label reel |
| Number per roll | 10 000 | |
| Operating temperature range | -40...150 °C | |
| Operating temperature range, max. | 150 °C | |
| Operating temperature range, min. | -40 °C | |
| Size of labelling field | 12 x 9 mm | |
| Type of printing | neutral | |
| UL 94 flammability rating | V-0 | |
| Version | Self-adhesive | |
| Width | 18 mm | |

Conductor and cable markers

| | | | |
|-------------------------------|----------------------|----------------------------------|--------------------------|
| Conductor O.D. | 1.9 - 1.9 mm | Conductor O.D., max. | 1,9 mm |
| Conductor O.D., min. | 1,9 mm | Conductor cross-section, max. | 6 mm ² |
| Conductor cross-section, min. | 0,75 mm ² | Cross-section for connected wire | 0.75 - 6 mm ² |
| Halogen | No | Text field height | 9 mm |
| Text field width | 12 mm | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| ETIM 8.0 | EC001530 | ETIM 9.0 | EC001530 |
| ECLASS 9.0 | 27-40-04-01 | ECLASS 9.1 | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |
| ECLASS 14.0 | 27-28-11-02 | | |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

Fiche de données**THM WO 12/18 WS**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Caractéristiques techniques**Approvals**

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|------------------------------------------|
| Engineering Data | CAD data – STEP |
| Catalogues | Catalogues in PDF-format |

Fiche de données

THM WO 12/18 WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Dessins

