

## 2510MCO3

Manual Starter, integral horsepower, NEMA M1, 600 VAC, 3 pole, 10 HP at 380/575 VAC, three phase, no indicator, open



### Principal

Product	Manual Starter
Type	M
NEMA Size	M-1

### Complémentaire

Control Unit	Bouton-poussoir
Pilot Light	Sans signalisation
Horsepower Rating	7,5 hpà 200 à 230 V AC, 3 phases 10 hpà 380...575 V AC, 3 phases
Voltage Rating	600 V AC
Number of Poles	3P
Starter Type	Non réversible
Electrical Connection	Pressure wire clamp
Overload Relay Type	Melting alloy
Number of Thermal Units Required	3
Wire Gauge	AWG 14...AWG 8 cuivre
Auxiliary Contacts	Sans
Hauteur	145,29 mm
Largeur	88,90 mm
Profondeur	102,36 mm
Poids	1,00 kg

### Environnement

Certifications	CSA LR60905 class 3211 05 UL listed file E42243 CCN NLRV
----------------	---

NEMA Enclosure Rating	Not rated (open device)
-----------------------	-------------------------

## Emballage

Poids de l'emballage (Kg)	997,903 g
Hauteur de l'emballage 1	16,510 cm
Largeur de l'emballage 1	12,700 cm
Longueur de l'emballage 1	22,352 cm

## Offre de la durabilité

Régulation REACH	<a href="#">Déclaration REACH</a>
Sans SVHC REACH	Oui
Directive RoHS UE	Conforme <a href="#">Déclaration RoHS UE</a>
Sans mercure	Oui
Information sur les exemptions RoHS	<a href="#">Oui</a>
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Sans PVC	Oui

## Garantie contractuelle

Garantie	18 months
----------	-----------