



## Principal

Product Type	Disjoncteur
Range	PowerPact M
Breaking Capacity Code	J
Trip Unit Technology	Électronique, basic, ET 1.0, LI

## Complémentaire

Current Sensor Rating Range	300 A
Rated Current	300 A
Rated Operational Voltage	600 V AC
Mounting Mode	I-Line
Poles Description	2P
Breaking Capacity	100 kA à 240 V AC 65 kA à 480 V AC 25 kA à 600 V AC
Circuit Breaker Type	M-frame
Continuous Current Rating	80 %
Electrical Connection	I-Line connection ligne Cosses charge
Magnetic Tripping Current	600...3000 A
Terminal Identifier	AL800M23K
AWG Gauge	AWG 3/0...500 kcmil (aluminium / cuivre) pour 3 câble(s)
Tightening Torque	50 N.m pour 95...240 mm <sup>2</sup> (AWG 3/0...500 kcmil)
Height	326,6 mm
Width	8,06 mm
Depth	210 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environnement

Certifications	CSA CEI Listé UL
----------------	------------------------

## Emballage

Poids de l'emballage (Kg)	12,701 kg
---------------------------	-----------

## Offre de la durabilité

Statut environnemental de l'offre	Produit Green Premium
Régulation REACH	<a href="#">Déclaration REACH</a>
Directive RoHS UE	Conforme <a href="#">Déclaration RoHS UE</a>
Sans mercure	Oui
Information sur les exemptions RoHS	<a href="#">Oui</a>
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Profil environnemental	<a href="#">Profil environnemental du Produit</a>
Profil de circularité	<a href="#">Informations de fin de vie</a>
Sans PVC	Oui

## Garantie contractuelle

Garantie	18 months
----------	-----------