



Principal

Product	Single Throw Safety Switch
Disconnect Type	Non-fusible disconnect
Number of Poles	3
Electrical Connection	Cosses
Duty Rating	Renforcé

Complémentaire

Line Rated Current	600 A
Factory Installed Neutral	None
Mounting Type	Saillie
Voltage Rating	600 V AC/DC
Wire Size	AWG 3/0...500 kcmil copper or aluminium
Puissance moteur hp	200 hp at 240 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 400 hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 500 hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 50 hp at 250 V DC 50 hp à 600 V DC
Hauteur	1277,87 mm
Largeur	708,15 mm
Profondeur	257,30 mm
Couple de serrage	42.37 N.m (AWG 3/0...500 kcmil)

Environnement

Certifications	CSA
Enclosure Rating	NEMA 3R galvanized steel

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Emballage

Poids de l'emballage (Kg)	88,451 kg
---------------------------	-----------

Offre de la durabilité

Statut environnemental de l'offre	Produit Green Premium
Régulation REACH	Déclaration REACH
Sans SVHC REACH	Oui
Directive RoHS UE	Conforme Déclaration RoHS UE
Sans mercure	Oui
Information sur les exemptions RoHS	Oui
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Profil environnemental	Profil environnemental du Produit
Sans PVC	Oui
Présence d'halogènes	Produit avec composants plastiques sans halogènes